System 500 **NEWTON 508** 8mm Cavity Drain Membrane



Rev 2.0 - 09 May 2018

PRODUCT CODE - M1, M2, M1R,& M2R

1. Identification of the Substance/Mixture and of the Company/Undertaking		
Product identifier		
Product name	Newton 508	
Product code	M1, M2, M1R, M2R & M3	
Relevant identified uses of the substa	nce and uses advised against	
Use of substance/mixture/article	8mm cavity drain membrane for waterproofing applications	
Details of the Supplier of the Materia	l Safety Data Sheet	
Company Address	Newton Waterproofing Systems, Newton House, 17-20 Sovereign Way, Tonbridge, Kent TN9 1RH	
• Web	www.newtonwaterproofing.co.uk	
Email address of the competent person info@newtonwaterproofing.co.uk		
Emergency telephone number	+44 (0)1732 360 095: 08:00/17:30 (GMT) Mon-Thur & 08:00/17:00 (GMT) Fri	
2. Hazards Identification		
• Refer to Section 16 for	The explanation of the abbreviations used throughout this MSDS The full list of Hazard Phrases stated throughout this MSDS	
2.1 Classification of the Product Ident	tifier	
Classification under CLP	Not Classified	
	Not hazardous to health when stored, handled and used in compliance with the following sections here	
• Most important adverse effects	If in a fire, melted material may adhere to skins and cause burns	
2.2 Label Elements	N/A	
2.3 Other Hazards		
• PBT / vPvB	NDA	
Other Hazards	During wet and freezing weather conditions the surface of the membrane may become slippery to foot traffic	
	Manual handling hazards to be managed. These products are supplied in rolls - 2m to 2.5m long (the width of the 40m opened roll) and with weights ranging from 24.5kg to 41.8kg	
3. Composition/Information	on Ingredients	
3.3 Article	Formed into sheets during production to achieve the designed Use, and in rolls sized for installation	
	Chemical family: HDPE	
Hazardous Substances	NDA, see Section 2.1 above	
NB	Please also refer to SECTION 8 Personal Protection / Exposure Controls	

Page 1 of 6

4. First Aid Measures

4.1 Description of First Aid Measures

General information	In case of persistent discomfort seek medical advice. For injuries when installing seek medical attention				
Skin contact	Wash cuts and apply bandage / plaster. Wash hands after use				
• Eye contact	Treat as foreign body, irrigate with eye wash or clean water				
Ingestion	Remove from mouth, do not swallow				
Inhalation	No specific measures. Seek medical advice if necessary				
4.2 Most Important Symptoms and	Effects, Both Acute and Delayed				
Skin contact	Risk of cuts from the edge of the membrane when profile cutting it to fit				
• Eye contact	NDA				
Ingestion	NDA				
Inhalation	NDA				
• Delayed / immediate effects	NDA				
4.3 Indication of Any Immediate Me	edical Attention and Special Treatment Needed				
• Immediate / special treatment	NDA				
5. Fire-Fighting Measures					
5.1 Extinguishing Media	Water, foam, dry chemical media				
5.2 Special Hazards Arising from the					
	If product combusts, water, carbon dioxide, carbon monoxide (in case of oxygen deficiency) and other organic compounds can be produced. At the beginning of the combustion (especially between 400°C-700°C) it may also generate hydrocarbons and aldehydes (acetic acid and crotonic acid)				
5.3 Advice for Firefighters	Wear breathing apparatus in confined spaces. Wear protective clothing to protect against burns				
6. Accidental Release Mease	ures				
6.1 Personal Precautions, Protective	6.1 Personal Precautions, Protective Equipment and Emergency Procedures				
	Wear cut resistant gloves when cutting the membrane. Always lay the membrane on a firm surface when cutting and cut away from self or other persons				
6.2 Environmental Precautions	Prevent the entry of HDPE particulates or remnants into the soil, surface water or groundwater. Sweep up and bag for disposal to recycling				
6.3 Methods and Materials for Cont	ainment and Cleaning Up				
	Always cut the membrane in a location where any particulates, off-cuts, remnants, etc. can be contained, collected up and bagged for disposal to recycling				
6.4 Reference to Other Sections	Refer to Section 8 of the MSDS				
7. Handling and Storage					
7.1 Precautions for Safe Handling					
	Manual Handling Defents Cestion 2.2 Oil - H				

a. Safe handling

NEWTON SYSTEM 500 - CAVITY DRAIN WATERPROOFING

Manual Handling - Refer to Section 2.3 Other Hazards above. Move using mechanical method or 2-person carrying. Comply with safe Manual Handling instructions and methods

Wear work gloves when handling against cuts from the edge, especially along the cut edge of a part roll Do not eat, drink or smoke when handling. Wash hands after using the material Prevention of handling incompatible substances or mixtures b. Do not handle other substances or mixtures at the same time. Keep away from other substances and mixtures Operations and conditions that could create new risks C. Ensure the rolls, including part rolls are securely tied / taped around against opening during movement by personnel and during transport Rolls to be securely placed in vehicles against falling onto other contents of the vehicles and onto personnel when opening the vehicles Should be noted when the product is handled and pneumatically transported (e.g. road vibration): VDI guideline 3673, 2263 (German - dust explosions). Fine particle material (< 0,125 mm) should not be allowed to accumulate, particularly when transported The product contains combustible polymers. The relevant fire protection measures thus apply Reduce risk of release to the environment d. NDA 7.2 Conditions for Safe Storage, Including Any Incompatibilities Storage conditions Store the rolls on end in the upright position and securely tied / taped / а. wrapped against opening. Store in an allocated area walling / fencing / etc. around against the risk of falling onto personnel or other items, or to block passageways Protect from sources of ignition, see Section 9 Physical & Chemical **Properties - Melting Point** Control of the effects of weather, ambient pressure, temperature, sunlight, humidity and vibration N/A, but best practice requires storage in a well ventilated area and away from direct sunlight and sources of ignition Storage with other substances and mixtures C. Store in an allocated area, and not mixed with or touching other materials Storage room design, quantity limits, ventilation and packaging compatibilities d. Storage room to be dry, cool, well ventilated, and protected from direct sunlight Other considerations Use of the stock must be by manufacturing date or expiry date or receipt e. date rotation, use the oldest first Ensure identification labelling is visible at all times Cavity drain membrane for waterproofing applications 7.3 Specific End Use(es) 8. Exposure Controls / Personal Protection 8.1 Control Parameters N/A, Not listed on the HSE EH40 Workplace Exposure Limit Table. **8.2 Exposure Controls** 8.2.1 Appropriate Engineering Controls N/A 8.2.2 Personal Protective Equipment Safety glasses with side protection EN166 when cutting to fit and when a. Eye / face protection drilling to attach to walls. Ensure eye bath facilities are available

b. Skin protection

9

0

Page 3 (

d.	Thermal hazards	N/A, no sources of ignition (see Section 7)
C.	Respiratory protection	N/A
		Good hygiene measures should be followed at all time
		Safety shoes / boots / safety helmet when carrying the membrane and when positioning to fix to walls - comply with site rules
	(ii) Other	Protective clothing
	Penetration time of gloves	N/A regarding the 508 membrane
		Gloves to protect against cuts when cutting and forming the membrane and abrasions, and to be suitable for protection against mortar if also laying brickwork, block-work, etc
		Gloves must be inspected prior to each time used and must be replaced when damaged or worn out
		Break through, and other characteristics, depending upon material density and the glove type, and must be determined in each case
		The selection of the suitable gloves does not only depend upon the material, but also further marks of quality and varies from manufacturer to manufacturer
	Material of gloves	The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC, this being repealed by EU 2016/425 on 21/04/2018, and the resultant standard EN 374
	(i) Hand Protection	

9. Physical and Chemical Properties

NEWTON SYSTEM 500 - CAVITY DRAIN WATERPROOFING

9.1 Information on Basic Physical and Chemical Properties

•	Appearance	
	(i) State	Solid sheet in roll form and film
	(ii) Colour	Various
٠	Odour	Essentially odourless
٠	Odour threshold	NDA
٠	pH in g/l H₂O	NDA
٠	Melting point/range °C	ca. 130°C
٠	Freezing point/range °C	NDA
٠	Initial boiling point/range °C	NDA
٠	Flash point/self-ignition °C	+/- 340°C
٠	Evaporation rate	NDA
٠	Flammability (solid, gas)	NDA
٠	Flammability limits, lower %	NDA
٠	Flammability limits, upper %	NDA
٠	Auto flammability °C	NDA
٠	Decomposition temperature	NDA
٠	Explosive properties	NDA
٠	Oxidising properties	NDA
٠	Vapour pressure	N/A
٠	Vapour density	NDA
٠	Relative density	956 kg/cm ³

(a trading name of John Newton & Co. Ltd.) Newton House, 17-20 Sovereign Way, Tonbridge, Kent, TN9 1RH

T: +44 (0)1732 360 095 W: www.newtonwaterproofing.co.uk E: tech@newtonwaterproofing.co.uk

NEWTON 508 8mm Cavity Drain Membrane

Solubility in water	Insoluble	
Partition coefficient n-octanol/wate	er NDA	
Also soluble in	NDA	
Viscosity	N/A	
• VOC g/l	N/A	
Explosive limits	upper n. a. Vol. % Iower n. a. Vol. %	
9.2 Other Information	N/A	
10. Stability and Reactivity		
10.1 Reactivity	Not known	
10.2 Chemical Stability	Chemically stable	
10.3 Possibility of Hazardous Reaction	s None	
10.4 Conditions to Avoid	Direct heat / naked flame, strong oxidising agents	
10.5 Incompatible Materials to Avoid	N/A	
10.6 Hazardous Decomposition Products	At ambient temperature - not known. At temperature above 300°C some degree of thermal degradation will occur, including the possible creation of airborne particulates	
11. Toxicological Information		
11.1 Information on Toxicological Effe	cts	
Acute toxicity	According to information available to us the product is not harmful to health provided it is correctly handled and processed according to the given recommendations	
12. Ecological Information		
12.1 Ecotoxicity	Not readily biodegradable. Particulates are not to be allowed to enter drains or water courses	
12.2 Persistence and Biodegradability	NDA	
12.3 Bioaccumulative Potential	NDA	
12.4 Mobility in Soil	NDA	
12.5 Results of PBT & vPvT Assessmen	t NDA	
12.6 Other Adverse Effects	NDA	

13. Disposal Considerations

13.1 Waste Treatment Methods

NEWTON SYSTEM 500 - CAVITY DRAIN WATERPROOFING

Recovery operations
Disposal operations
Disposal of packaging
Disposal of packaging
Treat as SECTION 6: Accidental Release Measures
Recycle uncontaminated material as HDPE waste, alternatively at approved waste collection sites as landfill or incinerate
Disposal of packaging
Plastic bag on delivered rolls when sent by National Carrier, otherwise by dedicated van with bag to rolls
Recycle or dispose of in accordance with appropriate government and local regulations

NEWTON 508 8mm Cavity Drain Membrane

Waste code number N/A Special precautions for the disposal method NDA NB The user's attention is drawn to the existence of regional and national regulations regarding recycling and disposal of plastic waste 14. Transport Information Transport The material is not hazardous for transport by sea, air and road/rail 15. Regulatory Information 15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture or Article COMMISSION REGULATION (EU) No 2015/830 of 28/05/2015 amend Regulation (EC) No 1907/2006 and repealing (EU) 453/2010 20 May 2010 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/ EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. **15.2 Chemical Safety Assessment** NDA 16. Other Information **Other Information** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship Phrases Used in Sections 2 & 3 N/A Notice The above mentioned data correspond to our present state of knowledge and experience. The safety data sheet serves as description of the products in regard to necessary safety measures. The indications have not the meaning of guarantees on properties. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Abbreviations & Acronyms MSDS: Material Safety Data Sheet N/A: Not Applicable NDA: No Data Available HDPE: High density polyethylene **Changes Compared to the Previous Version** An asterisk (*) to the left side indicates that there is a change to the previous version

9

Page 6 of