System 300 **NEWTON 322-SP Part A** Flexible Sealing Injection Resin

Mixture

322-SP

Newton 322-SP

Professional Use only

Not for any other use

Injection resin for waterproofing

Way, Tonbridge, Kent TN9 1RH

www.newtonwaterproofing.co.uk

info@newtonwaterproofing.co.uk

Newton Waterproofing Systems, Newton House, 17-20 Sovereign

+44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

safety practice. Wear PPE as SECTION 8.2, handle and store as SECTION

7, manage accidental release as SECTION 6 and follow the instructions in

Newton Waterproofing systems - English language



SECTION 1. Identification of the Substance/Mixture and of the Company/Undertaking WATERBARS, WATERSTOPS AND WATERPLUGS **Product Identifier** Product form Product name Product codes Relevant identified uses of the substance and uses advised against Use of substance/mixture Uses advised against Details of the Supplier of the Safety Data Sheet **Company Address** Web Email address of the competent person Emergency telephone numbers **SECTION 2. Hazards Identification** NEWTON SYSTEM 300 2.2 Label Elements

Refer to SECTION 16 for The explanation of the abbreviations used throughout this SDS The full list of Hazard Phrases & Precautionary Statements stated throughout this SDS 2.1 Classification of the Substance or Mixture Classification under Regulation (EC) No. 1272/2008 (CLP) Not classified Adverse physicochemical, human health and environmental effects To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practices Hazard statements No labelling applicable Signal words (CLP) N/A Hazard pictograms (CLP) N/A Hazardous ingredients N/A

- Hazard statements (CLP) N/A
- Precautionary statements (CLP)

2.3 Other Hazards

Other Hazards

- NDA

the Data Sheet

Other information

Classification and labelling have been made on the basis of safety data sheets of the raw materials that make up the product

Safety Data Sheet

SECTION 3. Composition/information on ingredients

3.2 Mixture

Ingestion

This product is a mixture

Hazardous Substances

Chemical name	CAS	EC No.	EC Index- No	REACH Registration Number	%	Classification accord- ing to Regulation (EC) No. 1272/2008 (CLP)
Polypropyleneglycol	25322- 69-4				10-20	Acute Tox. 4 (Oral), H322

NB

NEWTON SYSTEM 300 - WATERBARS, WATERSTOPS AND WATERPLUGS

Refer to SECTION 8 for Personal Protection / Exposure Controls

Refer to SECTION 16 for the full text of Hazard Statements

SECTION 4. First Aid Measures

4.1 Description of First Aid Measures

٠	General	Never give anything by mouth to an unconscious person. If exposed or concerned get medical advice / attention. If you feel unwell, seek medical advice
		Those assisting the exposed persons to take no action involving personal risk or without training. Performing mouth-to-mouth can be dangerous, only to be done by trained personnel
		Eye bathing equipment and First Aid Box should be available
		Take this SDS with you when seeking medial advice
٠	Skin contact	Remove contaminated clothing. Gently remove all traces of product and wash with plenty of soap and water. Continue to rinse for at least 10 minutes. If skin irritation or rash occurs seek medial advice / attention
٠	Eye contact	Do not rub. Immediately rinse eyes cautiously with plenty of water for at least 15 minutes holding the eyelids open. Remove contact lenses if present and easy to do so, then continue to rinse cautiously for 15 minutes. Obtain medical attention if pain, irritation, blinking or redness persists
•	Ingestion	Wash out mouth with water. Do NOT induce vomiting. Get emergency medical attention. If vomiting occurs, the head should be kept forward and low so vomit does not enter the lungs. Never give anything to an unconscious person. Move the exposed person to fresh air. If unconscious, place in the recovery position and get medical advice immediately. Loosen tight clothing such as collar, tie, belt and waistband. Call a doctor or poison centre if you feel unwell
•	Inhalation	Ventilate the area. Remove person from the contaminated place to rest in fresh air and keep comfortable and breathing. Assure fresh air breathing. Loosen tight clothing such as collar, tie, belt or waistband. If you feel unwell seek medical advice. Call a doctor or poison centre if you feel unwell
•	Self-protection for first aiders	No action to be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate Personal Protection Equipment, see SECTION 8.2. Wear gloves to remove contaminated clothing, see SECTION 13 for washing or disposal
4.2	Most Important Symptoms and Effe	ects, Both Acute and Delayed
•	Skin contact	May cause moderate irritation
•	Eye contact	May cause slight irritation

May be harmful if swallowed

(a trading name of John Newton & Co. Ltd.)

Newton House, 17-20 Sovereign Way, Tonbridge, Kent, TN9 1RH

T: +44 (0)1732 360095 W: www.newtonwaterproofing.co.uk E: info@newtonwaterproofing.co.uk

Page 3 of 24

Inhalation	May cause respiratory irritation
Delayed / immediate effects	NDA
4.3 Indication of Any Immediate Med	dical Attention and Special Treatment Needed
Immediate / special treatment	No specific treatment. Treat symptomatically
SECTION 5. Fire-Fighting Me	asures
5.1 Extinguishing Media	Powder, alcohol-resistant foam, dry power, carbon dioxide, water spray foam
	Unsuitable extinguishing media: - Do not use a heavy water stream
5.2 Special Hazards Arising from the	Material
	Toxic fumes may be released
5.3 Advice for Firefighters	Isolate the affected area
	All persons to be immediately removed from the vicinity of the fire. Fire to be dealt with by trained personnel and without involving personal risk
	Exercise caution when fighting any chemical fire
	Collect the fire fighting water separately. Prevent from entering the environment, waterways, sewers and drains, alert the Environmental Agency if this occurs
	Do not enter the area without wearing proper protective equipment, including respiratory protection
	Do not attempt to take action without suitable protective equipment. Self contained breathing apparatus. Complete protective clothing
SECTION 6. Accidental Relea	se Measures

6.1 Personal Precautions Protective Equipment and Emergency Procedures

rotective Equipin	ent una Emergency rioccaules
	not attempt to take action without wearing suitable personal protection, r to SECTION 8.2 of the SDS
Ensu	ire adequate ventilation
onnel Evac	uate unnecessary personnel
Do r	not touch or walk through the spilled material. Ventilate spillage area. not breathe dust / fumes/ gas / vapours / mist / spray. Avoid contact skin and eyes
prote bysta Mark	uate unnecessary personnel and those not wearing the suitable ection. If outside do not approach from downwind. If outside keep anders and passing persons upwind and away from the danger point. c out the contaminated area with signage and prevent access by othorised persons
clear	not attempt to take action without suitable protective equipment. Equip n-up crew with proper protection, see SECTION 8 'Exposure controls / onal protection'
spac	re adequate ventilation, including forced ventilation if in an internal e and necessary, and vent externally to be safely away from other ons and the general public
	leaking containers leak-side up to prevent the escape of material, and e in a sealable leak proof container, label this with the contents
Avoi	d inhalation of vapours, wear respiratory protection as SECTION 8.2
tions Prev	ent the product from entering drains, sewers or watercourses (refer to
	Do r refer Ensu Do r Do r Do r Do r With Evac prote bysta Mark unau Do n clear perso Ensu spac perso Turn plac

	SECTION 11). Contain the spillage using bunding
	Alert the Environmental Agency in the event of spillage, etc entering water ways, sewers or drains
6.3 Methods and Materials for Contain	nment and Cleaning Up
	Clean-up should ONLY be dealt with by qualified persons familiar with the specific product
	Stop the leak if it is safe to do so
	Large spillages should be contained by bunding using absorbent materials and carefully transferred into sealable impervious containers. Remnants from large spillages and small spillages should be absorbed and transferred into these containers
	Appropriate bunding / absorbent materials: sand, sawdust, universal absorbent and diatomaceous earth
	All washings to be retained within the bunding and fully collected up into sealable impervious waste container(s), label these with the contents
	All contaminated bunding, including all suspected of being contaminated, to be collected up and transferred to these waste containers
	All containers to be labelled and held for disposal as SECTION 13
6.4 Reference to Other Sections	Refer to SECTIONS 8 (Personal Protection / Exposure Controls), 12 (Ecological Information) and 13 (Disposal Consideration) of the SDS

SECTION 7. Handling and Storage

7.1 Precautions for Safe Handling

NEWTON SYSTEM 300 - WATERBARS, WATERSTOPS AND WATERPLUGS

	5	
a.	Safe handling	Wear protective equipment as required by use- see SECTION 8
		Do not get in eyes, on skin or on clothing - see SECTION 8 for the protection of work clothing. Obtain special instructions before use. Do not handle or use until all safety precautions have been read and understood. Only use outdoors or in well ventilated areas
		Do not breathe vapours, aerosols or gases
Э.	Hygiene measures	Do not eat, drink or smoke when handling. Wash hands and other exposed areas with mild soap and water after using the material and remove contaminated clothing and protective equipment before entering areas where food and drink are consumed and when leaving the work site
		Contaminated work clothing should not be allowed out of the work site. See SECTION 13 for the protection of work clothing and the washing or disposal of contaminated work clothing and boots
с.	Prevention of handling incompatible	e substances or mixtures
		Do not handle other substances or mixtures at the same time. Keep away from other substances and mixtures
d.	Operations and conditions that cou	d create new risks
		Do not allow opened, part used or the container in use to come into contact with other materials including all surfaces around. Ensure the containers are securely sealed during transport, storage and when at the work site
э.	Reduce risk of release to the enviror	nment
		Avoid spillage. Ensure the floor at storage, transport and the work location will not allow access to drains or water courses. Lay heavy gauge plastic sheeting or similarly impervious protective covering when mixing and dispensing. Contain and clean up spillage as SECTION 6.3 of the SDS

7.2 Conditions for Safe Storage, Including Any Incompatibilities

a.	Storage conditions	Store in a well ventilated locked area, keep cool and away from direct sunlight. Only store in original containers. Keep container tightly closed. The floor of the storage area to be impermeable to prevent the escape of spillage
b.	Maximum storage period	Maximum storage period (shelf life): 12 months from date of manufacture
		Use of the stock must be by manufacturing date or expiry date rotation. Containers past their expiry date must be removed for disposal according to SECTION 13 of the SDS
C.	Control of the effects of weather, an	nbient pressure, temperature, sunlight, humidity and vibration
		Protect from freezing, frost, heat and direct sunlight. Keep away from sources of ignition, open flames or excessive heat
		Ensure containers are securely closed against vibration spillage during transport when loading / unloading vehicles, during transport and moving from vehicle to the work location. Unopened containers to be protected against damage during these movements
d.	Storage with other substances and i	mixtures
		Only store in the original packaging. Store against falling / touching other materials and in an allocated location
		Store away from water
e.	Storage room design, quantity limits	s, ventilation and packaging compatibilities
		Storage room to be dry, ventilated, and constructed to have impermeable floors and walls to prevent the escape of spillages into the environment
f.	Other considerations	No other data available
7.3	Specific End Use(es)	An injection resin for waterproofing. Refer to the Technical Data Sheet for further information

SECTION 8. Personal Protection/Exposure Control

8.1 Control Parameters

Workplace Exposure Limits (WEL)	EH40: Taken from the HSE EH40/2005 (3rd edition, published 2018): - not stated = not on EH40 - if no 15 min STEL, 3x TWA used		
	 Carc: Capable of causing cancer and / or heritable genetic damage Sen: Capable of causing occupational asthma Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systematic toxicity 		

Substance & CAS	limit (8	n exposure hr TWA e period)	Short-term exposure limit (15 minute reference period)		Comments	Source
	ppm	mg / m³	ppm mg / m ³		The Carc, Sen and Sk notations are not exhaustive. Notations have been applied to substances identified in IOELV Directives	
Polypropyleneglycol						
25322-69-4	4 NDA - not on the EH40 Table HSE					

8.2 Exposure Controls

8.2.1 Appropriate Engineering Controls

a. Ventilation

Ensure there is sufficient ventilation in the area, including forced ventilation if necessary or in an internal or enclosed space, with safe exhaust away from

Page 5 of 24

Newton system 300 - waterbars, waterstops and waterplugs

b.

C.

d.

e.

f.

a.

b.

C.

- other persons. The floor must be impermeable to prevent the escape of liquids, laying impermeable protective covering if in doubt Isolation Isolate the work area with warning signage against unauthorised access. Ensure all other persons are pre-notified of the works and remain clear of the work area Washing Provide eye wash facilities, individual eye wash ampoules and safety shower Refer to SECTION 15.1 for any 'Other Regulations' and the REACH Annex Against contamination XVII statements there Only mix the 2 Parts of the product on impervious protective sheeting against splashes onto the person(s) performing this task, any other persons and onto the surrounding areas: When opening each Part and when progressively mixing them together When using the power mixer / paddle off a drill, include erecting barrier around if necessary to stop splashes off the protective sheeting onto other persons, structures, ground, etc The person(s) performing this to wear disposable overshoes over their safety work boots when working off the protective sheeting against walking contamination onto the surrounding area When the mixing is done, dispose of the contaminated protective sheeting, the overshoes, etc as controlled waste Mists Prevent the formation of vapour or aerosol Hygiene & Occupational care Do not eat, drink or smoke during stirring or use of the product. Wash hands with soap and water before eating, drinking or smoking and when leaving the work site for natural breaks, break times and at end of day 8.2.2 Personal Protective Equipment Work clothing Impervious disposable 1-piece covering to body, legs and arms with closure at wrists and ankles, and disposable overshoes Eye / face protection Tight fitting safety chemical goggles / safety glasses with side protection or face visor EN166 If at risk of splashing to face when mixing the 2-part product wear a full face visor Skin protection (i) Hand Protection To be impermeable and resistant to the product / substance / mixture. Due to missing tests no recommendation to the glove material can be given Selection of the glove material to be on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC, this being repealed by EU 2016/425 on 21/04/2018, and the resultant standard EN 374 The selection of the suitable gloves does not only depend upon the material, but also further marks of quality and varies from manufacturer to manufacturer Break through, and other characteristics, depending upon material density and the glove type, and must be determined in each case Gloves to be tightly fitting at the wrists and extend onto the disposable 1-piece covering. Cloves must be inspected prior to each time used and must be replaced when damaged or worn out Impervious gloves, chemical resistant: conforming to EN 374 Penetration time of gloves Breakthrough time of the glove material > 4 hours (ii) Other Chemical resistant safety boots with external feed for the laces, not holes for the laces
 - Safety helmet if required, or other head covering, against splashes

	Good hygiene measures should be followed at all time
Respiratory protection	Mouth & nose filter face mask to EN149:2001.
	In the case of inadequate ventilation wear an appropriate gas filter (i.e. type A according to EN 14387) is worn
	Mist formation; wear protection as for inadequate ventilation
Thermal hazards	NDA
Environmental exposure measures	Avoid release to the environment
Hygiene measures	Wash thoroughly after handling. Do NOT eat, drink or smoke while using this product. Remove contaminated clothing, see SECTION 13 for the washing or disposal of contaminated clothing
	Thermal hazards Environmental exposure measures

SECTION 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

			,		
•	Appearance	(i)	Form		Liquid
		(ii)	Colou	ır	Colourless
•	Odour				NDA
•	Odour threshold				NDA
•	рН				NDA
•	Melting point/range	e °C			N/A
•	Freezing point/rang	ge °(С		NDA
•	Initial boiling point,	/ran	ge °C		NDA
•	Flash point/self-ign	itio	n °C		NDA
•	Evaporation rate				NDA
•	Flammability (solid,	gas	5)		N/A
•	Flammability limits,	low	/er %		NDA
٠	Flammability limits,	up	oer %		NDA
•	Auto flammability °C				NDA
٠	Decomposition temperature			NDA	
•	Explosive properties				NDA
٠	Explosive limits			NDA	
•	Oxidising propertie	S			NDA
٠	Vapour pressure				NDA
٠	Relative vapour der	nsity	at 20°	С	NDA
٠	Relative density				1.005 g/ml
٠	Specific weight				NDA
٠	Solubility in water				NDA
٠	Partition coefficient	n-o	ctanol	/water	NDA
•	Also soluble in				NDA
•	Viscosity, kinematic				143.284 mm²/s
•	Viscosity, dynamic				144 mPa.s
•	VOC g/l				NDA
NC	DTE:				The above value for this product

The above values related to physiochemical properties are typical values for this product and should not, therefore, be construed as a specification

9.2 Other Information	NDA			
SECTION 10. Stability and Reactivity				
10.1 Reactivity	Stable under recommended transport or storage conditions Reacts with water			
10.2 Chemical Stability	Stable at room temperature, under recommended transport or storage conditions and when protected against the materials or conditions listed in SECTIONS 10.1 and 10.3			
10.3 Possibility of Hazardous Reaction	s No dangerous reactions known under normal conditions of use			
10.4 Conditions to Avoid	Moisture			
10.5 Incompatible Materials to Avoid	Strong oxidisers. May react violently with acids			
10.6 Hazardous Decomposition Products	Combustion: NDA Under normal conditions of storage and use, hazardous decomposition products should not be produced			

SECTION 11. Toxicological Information

11.1 Information on Toxicological Effects

Acute toxicity	Oral:	Not classified
	Dermal:	Not classified
	Inhalation:	Not classified

In the absence of experimental toxicological data on the product itself, the potential risks to health were evaluated based on the properties of the constituent substances, according to the criteria laid down by the relevant regulations for Classification

Hazardous ingredients

NEWTON SYSTEM 300 - WATERBARS, WATERSTOPS AND WATERPLUGS

Substance	Route	Test	Species	Value
CAS 25322-69-4 Polypropyleneglycol	Oral	LD50	Rat	1,000-2,000 mg/kg
	Dermal	LD50	Rabbit	> 10,000 mg/kg

Relevant hazards for product

Hazard	Negative Symptoms
Acute toxicity - oral	Harmful if swallowed

Other hazards

Hazard	Basis
Respiratory hazard / inhalation	Not classified
Serious eye damage / irritation	Not classified
Skin sensitisation	Not classified
Skin corrosion / irritation	Not classified
Carcinogenicity	Not classified
Germ cell mutagenicity	Not classified
Reproductive toxicity	Not classified
STOT single exposure	Not classified
STOT repeated exposure	Not classified
Acute toxicity - dermal	NDA
Acute toxicity - inhalation	NDA
Ingestion	NDA

Page 9 of 24

Aspiration hazard	Not classified
Viscosity, kinematic	143.284 mm²/s
Other information	The product was not tested. The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product
SECTION 12. Ecologic	al Information
12.1 Toxicity	

Environment

Aquatic toxicity

Not considered harmful to aquatic organisms nor to cause long-term ad verse effect to the environment Acute toxicity: Not classified

	Chronic toxicity:	Not classified
12.2 Persistence and Biodegradability	No additional inform	ation available
12.3 Bioaccumulative Potential	No additional informati	on available
12.4 Mobility in Soil	No additional informati	on available
12.5 Results of PBT & vPvT Assessment	: No additional informati	on available
12.6 Other Adverse Effects	Avoid release to the en	vironment
	No additional informati	on available
12.7 Additional information	manufacturer's SDS whi	sted. The data reported here are based on the ch is based on information contained in the safety naterials that make up the product
	No other information a	vailable

No other information available

SECTION 13. Disposal Considerations

13.1 Waste Treatment Methods

•	Recovery operations	Treat as SECTION 6: Accidental Release	Measures
		NOTE: The surface can skin over leaving the ma	terial below in its liquid state
•	Disposal operations	Dispose at approved waste collection sites as co	ontrolled waste
•	Disposal of packaging	Metallic 12L drum with cap inset into the top fa internally to clean, dispose to controlled waste or recycling if possible by them	
•	Waste code number	Product: Packaging Metal drum with resin remnants:	17 09 03* 17 04 09*
•	Special precautions for the disposal	method	
		Ensure substances or mixtures are not mixed wi held in the same outer container with other may sealed containers within the outer container	

• NB

The user's attention is drawn to the possible existence of regional or national regulations regarding disposal

SECTION 14. Transport Information

ADR	IMDG IATA ADN		ADN	RID
14.1 UN Number				
N/A	N/A	N/A	N/A	N/A

N/A	N/A	N/A	N/A	N/A
14.3 Transport hazard cla	ss(es)			
N/A	N/A	N/A	N/A	N/A
14.4 Packing group				
N/A	N/A	N/A	N/A	N/A
14.5 Environmental hazar	ds			
N/A	N/A	N/A	N/A	N/A
No supplementary inform	nation available			
4.6 Special Precautions fo	or User			
Overland transport	N/A			
Transport by sea	N/A			
Air transport	N/A			
Inland waterway trans	port N/A			
inana waterway trans				
Rail transport	N/A			
· · · · · · · · · · · · · · · · · · ·				
Rail transport	cording to:			

SECTION 15. Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture or Article

COMMISSION REGULATIONS (EC) No 1272/2008 and (EU) No 2015/830 of 28/05/2015 amending Regulation (EC) No 1907/2006 and repealing (EU) 453/2010 20 May 2010 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Other regulations, limitations and prohibitive regulations

Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances Directive 2012/18/EU (SEVESO III) A chemical safety assessment has not been carried out. Data from the

component substances is included in this SDS

SECTION 16. Other Information

15.2 Chemical Safety Assessment

16.1 Basis of this SDS

The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

16.2 Changes Compared to the Previous Version

Date	Replaces	Sections	Item	Change	Comment
27/02/19	N/A				This is the 1st issue, read the entire document

16.3 Key literature and sources of data	Regulation (EC) 1907/2006 Regulation (EC) No. 1272/2008 Regulation (EU) No. 2015/830 Supplier SDS ECHA, including REACH dossier for component substances EH40/2005 3rd Edition, 2018
16.4 Abbreviations & Acronyms	CLP: EU Regulation 1272/2008: Classification, Labelling & packaging of chemical substances
	EINECS: European Inventory of Existing Commercial Chemical Substances or European List of Notified Chemical Substance number HSE: (UK) Health & Safety Executive
	IBC Code: International Building Code
	LD50: Lethal dose, 50% affected
	MARPOL: International Convention for the Prevention of Pollution from Ships
	N/A: Not Applicable
	NDA: No Data Available
	PBT: Persistent, Bioaccumulative and Toxic substances
	vPvB: Very Persistent and very Bioaccumulative substances
	REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals: Regulation (EC) No 1907/2006
	SDS: Safety Data Sheet
	STEL: Short Term Exposure Limit
	STOT RE: Specific target organ toxicity (from) repeated exposure
	STOT SE: Specific target organ toxicity (from) single exposure
	TWA: Time Weighted Averages
	VOC: Volatile organic compounds

16.5 Full text of H and EUH statements

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
H302	Harmful if swallowed	
16.6 Training advice	Obtain special instructions and read the Safety Data Sheet before use. Do not handle until all safety precautions have been read and understood. It is recommended that workers are trained in the safe handling of hazardous	

chemicals

16.7 DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best on the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to is accuracy, reliability or completeness. It is the users responsibility to satisfy themselves as to the suitability of such information for their own particular use

System 300 **NEWTON 322-SP Part B** Flexible Sealing Injection Resin



	Rev 1.0 - 28 February
S	SECTION 1. Ide
ATERSTOPS AND WATERPLUGS	 Product Identifier Product form Product name Product codes Relevant identified of Use of substance Uses advised age Details of the Suppl Company Addres Web Email address of Emergency telep
Š	SECTION 2. Ha
BARS	Refer to SECTION
- WATERI	2.1 Classification ofClassification un
VTON SYSTEM 300 -	• Adverse physico

entification of the Substance/Mixture and of the Company/Undertaking

- Mixture
- Newton 322-SP
- 322-SP

uses of the substance and uses advised against

- e/mixture Professional use only Injection resin for waterproofing
- ainst Not for any other use
- lier of the Safety Data Sheet
- ess Newton Waterproofing Systems, Newton House, 17-20 Sovereign Way, Tonbridge, Kent TN9 1RH
- www.newtonwaterproofing.co.uk
- the competent person
 - info@newtonwaterproofing.co.uk
- Newton Waterproofing systems English language phone numbers +44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

zards Identification

N 16 for The explanation of the abbreviations used throughout this SDS The full list of Hazard Phrases & Precautionary Statements stated throughout this SDS

the Substance or Mixture

der Regulation (EC) No. 1272/2008 (CLP)

)	INO. 12/2/2000 (CLI)	
	Skin Irrit. 2	H315
	Skin Sens. 1	H317
	Eye Irrit. 2,	H319
	Acute Tox 4 (Inhalation: dust, mist)	H332
	Resp. Sens. 1	H334
	Carc. 2	H351
	STOT SE 3	H335
	STOT RE 2	H373
	Full text of hazard classes and H-stater	nents: see SECTION 16

chemical, human health and environmental effects

Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled

2.2 Label Elements

111

- Hazard statements
- As 2.1 Classification under CLP

Danger

Signal words (CLP)

NEWTON 322-SP Part B Flexible Sealing Injection Resin

Hazard pictograms (CLP)



- Hazardous ingredients
- Hazard statements (CLP)

Diphenylmethane-4,4'-diisocyanate

Diphenylmethanediisocyanate, isomers and homologues

- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335 May cause respiratory irritation
- H351 Suspected of causing cancer
- H373 May cause damage to organs through prolonged or repeated exposure
- Precautionary statements (CLP)

EUH statements

Other

2.3 Other Hazards PBT / vPvB

Other Hazards

Other information

- P260 Do not breathe dust, fume, gas, mist, spray, vapours Wear protective gloves / clothing and eye / face protection P280 P302+P352 IF ON SKIN: Wash with plenty of water
 - P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
 - P305+P351 IF IN EYES: Rinse cautiously with water for several minutes. +P338 Remove contact lenses, if present and easy to do. Continue rinsina
 - P333+P313 If skin irritation or rash occurs: Get medical advice / attention P501 Dispose of contents / container to hazardous or special
 - waste collection point, in accordance with local, regional, national and/or international regulation
 - EUH204 Contains isocyanates: May produce an allergic reaction

To be handled and used in accordance with good occupational hygiene and safety practice. Wear PPE as SECTION 8.2, handle and store as SECTION 7, manage accidental release as SECTION 6 and follow the instructions in the Data Sheet

No additional information available

NDA

Classification and labelling have been made on the basis of safety data sheets of the raw materials that make up the product

Page 13 of 24

SECTION 3. Composition/information on ingredients

3.2 Mixture

This product is a mixture

Hazardous Substances

Chemical name	CAS	EC No.	EC Index- No	REACH Registration Number	%	Classification accord- ing to Regulation (EC) No. 1272/2008 (CLP)
Diphenylmethane-4,4'- diisocyanate	101-68-8	202- 966-0	615- 005-0-9	01- 2119457014- 47	20-40	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4 (inhalation), H332 Acute Tox. 4 (inhalation dust, mist), H332 Resp. Sens. 1, H334 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Diphenylmethanediisocyanate, isomers and homologues	9016- 87-69			01- 2119457014- 47	40-70	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, (inhalation), H332 Resp. Sens. 1, H334 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

	Specific Concentration Limits			
Chemical Name	CAS	EC No	REACH Registration Number	Specific concentration Limits
Diphenylmethane-4,4'-diisocyanate	101- 68-8	202- 966-0	01- 2119457014- 47	$(C \ge 0.1\%)$ Resp. Sens. 1, H334 ($C \ge 5\%$) Skin Irrit. 2, H315 ($C \ge 5\%$) Eye Irrit. 2, H319 ($C \ge 5\%$) STOT SE 3, H335

NB

Refer to SECTION 8 for Personal Protection / Exposure Controls

Refer to SECTION 16 for the full text of Hazard Statements

SECTION 4. First Aid Measures

4.1 Description of First Aid Measures

General

Skin contact

Never give anything by mouth to an unconscious person. If exposed or concerned get medical advice / attention. If you feel unwell, seek medical advice

Those assisting the exposed persons to take no action involving personal risk or without training. Performing mouth-to-mouth can be dangerous, only to be done by trained personnel

Eye bathing equipment and First Aid Box should be available

Take this SDS with you when seeking medial advice

Remove contaminated clothing. Gently remove all traces of product and wash with plenty of soap and water. Continue to rinse for at least 10 minutes. If skin irritation or rash occurs seek medial advice / attention

•	Eye contact	Do not rub. Immediately rinse eyes cautiously with plenty of water for at least 15 minutes holding the eyelids open. Remove contact lenses if present and easy to do so, then continue to rinse cautiously for 15 minutes. Obtain medical attention if pain, irritation, blinking or redness persists			
•	Ingestion	Wash out mouth with water. Do NOT induce vomiting. Get emergency medical attention. If vomiting occurs, the head should be kept forward and low so vomit does not enter the lungs. Never give anything to an unconscious person. Move the exposed person to fresh air. If unconscious, place in the recovery position and get medical advice immediately. Loosen tight clothing such as collar, tie, belt and waistband. Call a doctor or poison centre if you feel unwell			
•	Inhalation	Ventilate the area. Remove person from the contaminated place to rest in fresh air and keep comfortable and breathing. Assure fresh air breathing. Loosen tight clothing such as collar, tie, belt or waistband. If you feel unwell seek medical advice. Call a doctor or poison centre if you feel unwell			
٠	Self-protection for first aiders	No action to be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate Personal Protection Equipment, see SECTION 8.2. Wear gloves to remove contaminated clothing, see SECTION 13 for washing or disposal			
4.2	Most Important Symptoms and Eff	ects, Both Acute and Delayed			
٠	Skin contact	Causes skin irritation. Irritation. May cause and allergic reaction			
٠	Eye contact	Causes serious eye irritation. Eye irritation			
٠	Ingestion	May be harmful if swallowed			
•	Inhalation	Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled			
٠	Delayed / immediate effects	NDA			
4.3	Indication of Any Immediate Medie	cal Attention and Special Treatment Needed			
٠	Immediate / special treatment	No specific treatment. Treat symptomatically			
S	ECTION 5. Fire-Fighting Mea	isures			
5.1	. Extinguishing Media	Water spray, dry powder, carbon dioxide, foam			
		Unsuitable extinguishing media: Do not use a heavy water stream			
5.2	Special Hazards Arising from the M	1aterial			
		Toxic fumes may be released			
5.3	Advice for Firefighters	Isolate the affected area			
		All persons to be immediately removed from the vicinity of the fire. Fire to be dealt with by trained personnel and without involving personal risk			
		Exercise caution when fighting any chemical fire			
		Collect the fire fighting water separately. Prevent from entering the environment, waterways, sewers and drains, alert the Environmental Agency if this occurs			
		Do not enter the area without wearing proper protective equipment, including respiratory protection			
		Do not attempt to take action without suitable protective equipment. Self contained breathing apparatus. Complete protective clothing			
S	ECTION 6. Accidental Releas	e Measures			

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

- General measures
- Do not attempt to take action without wearing suitable personal protection,

	refer to SECTION 8.2 of the SDS
	Ensure adequate ventilation
Non-emergency personnel	Evacuate unnecessary personnel
	Do not touch or walk through the spilled material. Ventilate spillage area. Do not breathe dust / fumes/ gas / vapours / mist / spray. Avoid contact with skin and eyes
Emergency personnel	Evacuate unnecessary personnel and those not wearing the suitable protection. If outside do not approach from downwind. If outside keep bystanders and passing persons upwind and away from the danger point. Mark out the contaminated area with signage and prevent access by unauthorised persons
	Do not attempt to take action without suitable protective equipment. Equip clean-up crew with proper protection, see SECTION 8 'Exposure controls / personal protection'
	Ensure adequate ventilation, including forced ventilation if in an internal space and necessary, and vent externally to be safely away from other persons and the general public
	Turn leaking containers leak-side up to prevent the escape of material, and place in a sealable leak proof container, label this with the contents
	Avoid inhalation of vapours, wear respiratory protection as SECTION 8.2
6.2 Environmental Precautions	Prevent the product from entering drains, sewers or watercourses (refer to SECTION 11). Contain the spillage using bunding
	Alert the Environmental Agency in the event of spillage, etc entering water ways, sewers or drains
6.3 Methods and Materials for Cont	tainment and Cleaning Up
	Clean-up should ONLY be dealt with by qualified persons familiar with the specific product
	Stop the leak if it is safe to do so
	Large spillages should be contained by bunding using absorbent materials and carefully transferred into sealable impervious containers. Remnants from large spillages and small spillages should be absorbed and transferred into these containers
	Appropriate bunding / absorbent materials: sand, sawdust, universal absorbent and diatomaceous earth
	All washings to be retained within the bunding and fully collected up into sealable impervious waste container(s), label these with the contents
	All contaminated bunding, including all suspected of being contaminated, to be collected up and transferred to these waste containers
	All containers to be labelled and held for disposal as SECTION 13

SECTION 7. Handling and Storage

7.1 Precautions for Safe Handling

a. Safe handling

Persons already sensitised to diisocyantes may develop allergic reactions when using this product

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product

Wear protective equipment as required by use- see SECTION 8

		Do not get in eyes, on skin or on clothing - see SECTION 8 for the protection of work clothing. Obtain special instructions before use. Do not handle or use until all safety precautions have been read and understood. Only use outdoors or in well ventilated areas	
		Do not breathe vapours, aerosols or gases	
b.	Hygiene measures	Do not eat, drink or smoke when handling. Wash hands and other exposed areas with mild soap and water after using the material and remove contaminated clothing and protective equipment before entering areas where food and drink are consumed and when leaving the work site	
		Contaminated work clothing should not be allowed out of the work site. See SECTION 13 for the protection of work clothing and the washing or disposal of contaminated work clothing and boots	
C.	Prevention of handling incompatibl	e substances or mixtures	
		Do not handle other substances or mixtures at the same time. Keep away from other substances and mixtures	
d.	Operations and conditions that cou	ıld create new risks	
		Do not allow opened, part used or the container in use to come into contact with other materials including all surfaces around. Ensure the containers are securely sealed during transport, storage and when at the work site	:
e.	Reduce risk of release to the enviro	nment	
		Avoid spillage. Ensure the floor at storage, transport and the work location will not allow access to drains or water courses. Lay heavy gauge plastic sheeting or similarly impervious protective covering when mixing and dispensing. Contain and clean up spillage as SECTION 6.3 of the SDS	
7.2	Conditions for Safe Storage, Includ	ling Any Incompatibilities	
a.	Storage conditions	Store in a well ventilated locked area, keep cool and away from direct sunlight. Only store in original containers. Keep container tightly closed. The floor of the storage area to be impermeable to prevent the escape of spillage	
b.	Maximum storage period	Maximum storage / use period: Refer to the 'Best Before' date on the container label	
		Use of the stock should be by Best Before date rotation, using the oldest dates first. Containers past their Best Before date should be removed for disposal according to SECTION 13 of the SDS	
С.	Control of the effects of weather, an	nbient pressure, temperature, sunlight, humidity and vibration	
		Protect from freezing, frost, heat and direct sunlight. Keep away from sources of ignition, open flames or excessive heat	
		Ensure containers are securely closed against vibration spillage during transport when loading / unloading vehicles, during transport and moving from vehicle to the work location. Unopened containers to be protected against damage during these movements	
d.	Storage with other substances and	mixtures	
		Only store in the original packaging. Store against falling / touching other materials and in an allocated location	
e.	Storage room design, quantity limit	s, ventilation and packaging compatibilities	
		Storage room to be dry, ventilated, and constructed to have impermeable floors and walls to prevent the escape of spillages into the environment	24
f.	Other considerations	No other data available	of 24
7.3	Specific End Use(es)	An injection resin for waterproofing. Refer to the Technical Data Sheet for further information	Page 17

© Newton Waterproofing Systems (*a trading name of John Newton & Co. Ltd.*) Newton House, 17-20 Sovereign Way, Tonbridge, Kent, TN9 1RH T: +44 (0)1732 360095 W: www.newtonwaterproofing.co.uk E: info@newtonwaterproofing.co.uk

SECTION 8. Personal Protection/Exposure Control

8.1 Control Parameters

Workplace Exposure Limits (WEL)

EH40: Taken from the HSE EH40/2005 (3rd edition, published 2018): - not stated = not on EH40

- if no 15 min STEL, 3x TWA used

Carc: Capable of causing cancer and / or heritable genetic damage Sen: Capable of causing occupational asthma

Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systematic toxicity

Substance & CAS	Long-term exposure limit (8hr TWA reference period)		Short-term exposure limit (15 minute reference period)		Comments	Source
	ppm	mg / m³	ppm	mg / m³	The Carc, Sen and Sk notations are not exhaustive. Notations have been applied to substances identified in IOELV Directives	
Diphenylmetl	Diphenylmethanediisocyanate, isomers and homologues					
9016-87-9	-	0.02	-	0.07	Sen	EH40 Isocyanates
Diphenylmet	Diphenylmethane-4,4'-diisocyanate					
101-68-8	-	0.02	-	0.07	Sen	EH40 Isocyanates

8.2 Exposure Controls

8.2.1 Appropriate Engineering Controls

a. Ventilation Ensure there is sufficient ventilation in the area, including forced ventilation if necessary or in an internal or enclosed space, with safe exhaust away from other persons. The floor must be impermeable to prevent the escape of liquids, laying impermeable protective covering if in doubt Isolation Isolate the work area with warning signage against unauthorised access. b. Ensure all other persons are pre-notified of the works and remain clear of the work area Provide eye wash facilities, individual eye wash ampoules and safety shower Washing C. d. Against contamination Refer to SECTION 15.1 for any 'Other Regulations' and the REACH Annex XVII statements there Single-Part product, stirring is not required. Work and dispence off impervious protective sheeting against splashes onto the person(s) performing this task, any other persons and onto the surrounding areas: The person(s) performing this to wear disposable overshoes over their safety work boots when working off the protective sheeting against walking contamination onto the surrounding area When the application is done, dispose of contaminated protective sheeting, the overshoes, etc as controlled waste Mists Prevent the formation of vapour or aerosol e. f. Hygiene & Occupational care Do not eat, drink or smoke during stirring or use of the product. Wash hands with soap and water before eating, drinking or smoking and when leaving the work site for natural breaks, break times and at end of day 8.2.2 Personal Protective Equipment a. Work clothing Impervious disposable 1-piece covering to body, legs and arms with closure at wrists and ankles, and disposable overshoes

Page 18 of 24

NEWTON 322-SP Part B Flexible Sealing Injection Resin

b.	Eye / face protection	Tight fitting safety goggles, safety glasses with side protection or face visor EN166
C.	Skin protection (i) Hand Protection	To be impermeable and resistant to the product / substance / mixture. Due to missing tests no recommendation to the glove material can be given Selection of the glove material to be on consideration of the penetration times, rates of diffusion and the degradation
	Material of gloves	The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC, this being repealed by EU 2016/425 on 21/04/2018, and the resultant standard EN 374
		The selection of the suitable gloves does not only depend upon the material, but also further marks of quality and varies from manufacturer to manufacturer
		Break through, and other characteristics, depending upon material density and the glove type, and must be determined in each case
		Gloves to be tightly fitting at the wrists and extend onto the disposable 1-piece covering. Cloves must be inspected prior to each time used and must be replaced when damaged or worn out
		Impervious gloves, chemical resistant: conforming to EN 374
	Penetration time of gloves	Breakthrough time of the glove material > 4 hours
	(ii) Other	Chemical resistant safety boots with external feed for the laces, not holes for the laces
		Safety helmet if required, or other head covering, against splashes
		Good hygiene measures should be followed at all time
d.	Respiratory protection	Mouth & nose filter face mask to EN149:2001.
		In the case of inadequate ventilation wear an appropriate gas filter (i.e. type A according to EN 14387) is worn
		Mist formation; wear protection as for inadequate ventilation
e.	Thermal hazards	NDA
f.	Environmental exposure measures	Avoid release to the environment
g.	Hygiene measures	Wash thoroughly after handling. Do NOT eat, drink or smoke while using this product. Remove contaminated clothing, see SECTION 13 for the washing or disposal of contaminated clothing

SECTION 9. Physical and Chemical Properties

NEWTON SYSTEM 300 - WATERBARS, WATERSTOPS AND WATERPLUGS

9.1 Information on Basic Physical and Chemical Properties

٠	Appearance	(i) Form	Liquid
		(ii) Colour	Brown
٠	Odour		Characteristic odour
٠	Odour threshold		NDA
٠	рН		NDA
٠	Melting point/range °C		N/A
٠	Freezing point/range °C		NDA
٠	Initial boiling point/range °C		NDA
٠	Flash point/self-ignition °C		NDA
٠	Evaporation rate		NDA
٠	Flammability (solid, gas)		N/A

© Newton Waterproofing Systems (a trading name of John Newton & Co. Ltd.)

Newton House, 17-20 Sovereign Way, Tonbridge, Kent, TN9 1RH

T: +44 (0)1732 360095 W: www.newtonwaterproofing.co.uk E: info@newtonwaterproofing.co.uk

٠	Flammability limits, lower %	NDA
٠	Flammability limits, upper %	NDA
٠	Auto flammability °C	NDA
٠	Decomposition temperature	NDA
٠	Explosive properties	NDA
٠	Explosive limits	NDA
٠	Oxidising properties	NDA
٠	Vapour pressure	NDA
٠	Relative vapour density at 20°C	NDA
٠	Relative density	1.105 g/ml
٠	Specific weight	NDA
٠	Solubility in water	NDA
٠	Partition coefficient n-octanol/water	NDA
٠	Also soluble in	NDA
٠	Viscosity, kinematic	56.109 mm²/s
٠	Viscosity, dynamic	62 mPa.s
٠	VOC g/l	NDA
N	OTE:	The above values related to physiochemical properties are typical values for this product and should not, therefore, be construed as a specification
9	2 Other Information	NDA
	SECTION 10 Stability and Rea	ctivity

SECTION 10. Stability and Reactivity

10.1 Reactivity	Stable under recommended transport or storage conditions
	Reacts with water
10.2 Chemical Stability	Stable at room temperature, under recommended transport or storage conditions and when protected against the materials or conditions listed in SECTIONS 10.1 and 10.3
10.3 Possibility of Hazardous Reactions	No dangerous reactions known under normal conditions of use
10.4 Conditions to Avoid	High temperatures. Moisture
10.5 Incompatible Materials to Avoid	No additional information available
10.6 Hazardous Decomposition oxides Products	During combustion: carbon dioxide, carbon monoxide, nitrogen

SECTION 11. Toxicological Information

11.1 Information on Toxicological Effects

Acute toxicity

NEWTON SYSTEM 300 - WATERBARS, WATERSTOPS AND WATERPLUGS

Harmful if inhaled

In the absence of experimental toxicological data on the product itself, the potential risks to health were evaluated based on the properties of the constituent substances, according to the criteria laid down by the relevant regulations for Classification

ATE (Acute Toxicity Estimates) under CLP			
Dust, mist	1.557 mg/L/4hr		

Hazardous ingredients

Substance	Route	Test	Species	Value
CAS 101-68-8 Diphenylmethane-4,4'-diisocyanate	Oral	LD50	Rat	>10,000 mg/kg
	Dermal	LD50	Rabbit	> 9,400 mg/kg
	Inhalation	LD50	Rat (mg/L)	0.49 mg/L/4hr
CAS 9016-87-9 Diphenylmethanediisocyanate, isomers and	Oral	LD50	Rat	>10,000 mg/kg
homologues	Dermal	LD50	Rabbit	>9,400 mg/kg
	Inhalation	LD50	Rat (mg/L)	0.31 mg/L/4hr

Hazard	Negative Symptoms		
Respiratory hazard / inhalation	May cause allergy or asthma symptoms or breathing difficulties if inhaled		
Serious eye damage / irritation	Causes serious eye irritation		
Skin sensitisation	May cause an allergic skin reaction		
Skin corrosion / irritation	Causes skin irritation		
Carcinogenicity	Suspected of causing cancer		
STOT single exposure	May cause respiratory irritation		
STOT repeated exposure	epeated exposure May cause damage to organs through prolonged or repeated exposure		

Other hazards

NEWTON SYSTEM 300 - WATERBARS, WATERSTOPS AND WATERPLUGS

Hazard	Basis		
Acute toxicity - oral	NDA		
Acute toxicity - dermal	NDA		
Acute toxicity - inhalation	NDA		
Ingestion	NDA		
Germ cell mutagenicity	Not classified		
Reproductive toxicity	Not classified		
Aspiration hazard	Not classified		
Viscosity, kinematic	56.109 mm²/s		
Other information	The product was not tested. The data reported here are based on the manufacturers' SDS which is based on information contained in the safety		

data sheets of the raw materials that make up the product

SECTION 12. Ecological Information

12.1 Toxicity				
Environment	Not considered harmful to aquatic organisms nor to cause long-term ad verse effect to the environment			
Aquatic toxicity	Acute toxicity:	Not classified		
	Chronic toxicity:	Not classified		
12.2 Persistence and Biodegradability	No additional information available			
12.3 Bioaccumulative Potential	No additional informatin available			
12.4 Mobility in Soil	No additional information available			
12.5 Results of PBT & vPvT Assessment	t No additional informat	tion available		
12.6 Other Adverse Effects	NDA			
	Avoid release to the er	nvironment		
12.7 Additional information	The product was not te	ested. The data reported here are based on the		

<u>T: +44 (0)1732 360095</u> W: www.newtonwaterproofing.co.uk E: info@newtonwaterproofing.co.uk

manufacturers' SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

No other information available

SECTION 13. Disposal Considerations

13.1 Waste Treatment Methods

Recovery operations Treat as SECTION 6: Accidental Release Measures
 Disposal operations Dispose at approved waste collection sites as controlled waste
 Disposal of packaging Metallic 13.2L drum with cap inset into the top face so cannot access internally to clean, dispose to controlled waste disposal and including metal recycling if possible by them
 Waste code number Part B and wet & solidified mixed Part A+Part B: 17 09 03* Packaging Metal drum with resin remnants: 17 04 09*
 Special precautions for the disposal method

Ensure substances or mixtures are not mixed with other materials and if held in the same outer container with other materials all are in separate sealed containers within the outer container

NB
 The user's attention is drawn to the possible existence of regional or national regulations regarding disposal

SECTION 14. Transport Information

ADR	IMDG	IATA	ADN	RID
14.1 UN Number	·		•	
N/A	N/A	N/A	N/A	N/A
14.2 UN proper shipping na	ame			
N/A	N/A	N/A	N/A	N/A
14.3 Transport hazard class	(es)			
N/A	N/A	N/A	N/A	N/A
14.4 Packing group				
N/A	N/A	N/A	N/A	N/A
14.5 Environmental hazards	5			
N/A	N/A	N/A	N/A	N/A
No supplementary informa	tion available			
1.6 Special Precautions for	User			
• Overland transport	N/A			
Transport by sea	N/A			
Air transport N/A				
Inland waterway transpo	ort N/A			
Rail transport	N/A			

14.7 Transport in Bulk According to:

(i) Annex II of Marpol N/A (ii) the IBC Code N/A

SECTION 15. Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture or Article

COMMISSION REGULATIONS (EC) No 1272/2008 and (EU) No 2015/830 of 28/05/2015 amending Regulation (EC) No 1907/2006 and repealing (EU) 453/2010 20 May 2010 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Other regulations, limitations and prohibitive regulations

When the information contained within the SDS is complied with the product contains no REACH substances with Annex XVII restrictions Contains no substances on the REACH candidate list Contains no REACH Annex 14 substance Directive 2012/18/EU (SEVESO III) A chemical safety assessment has not been carried out. Data from the

component substances is included in this SDS

SECTION 16. Other Information

15.2 Chemical Safety Assessment

16.1 Basis of this SDS

NEWTON SYSTEM 300 - WATERBARS, WATERSTOPS AND WATERPLUGS

The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

16.2 Changes Compared to the Previous Version

Date	Replaces	Sections	Item	Change	Comment
27/02/19	N/A				This is the 1st issue, read the entire document
.6.3 Key lite	erature and	sources of c	lata Regulation (EC) 1907/2006 Regulation (EC) No. 1272/200 Regulation (EU) No. 2015/830 Supplier SDS ECHA, including REACH doss EH40/2005 3rd Edition, 2018	D	nent substances
.6.4 Abbrev	viations & A	Acronyms	 CLP: EU Regulation 1272/200 chemical substances HSE: (UK) Health & Safety Exe IBC Code: International Build LD50: Lethal dose, 50% affect MARPOL: International Conversions N/A: Not Applicable NDA: No Data Available PBT: Persistent, Bioaccumulat vPvB: Very Persistent and ver REACH: Registration, Evaluati Chemicals: Regulatio SDS: Safety Data Sheet STEL: Short Term Exposure Li STOT RE: Specific target orga 	ecutive ing Code ted ention for the ive and Toxic y Bioaccumula on, Authorisa n (EC) No 190 mit	substances ative substances tion and Restriction of 17/2006
			STOT SE: Specific target orga		

T: +44 (0)1732 360095 W: www.newtonwaterproofing.co.uk E: info@newtonwaterproofing.co.uk

TWA: Time Weighted Averages VOC: Volatile organic compounds

16.5 Full text of H and EUH statements

Acute toxicity (Inhalation), Category 4
Acute toxicity (Inhalation: dust, mist), Category 4
Carcinogenicity, Category 2
Serious eye damage / irritation, Category 2
Respiratory sensitisation, Category 1
Skin corrosion / irritation, Category 2
Skin sensitisation, Category 1
Specific target organ toxicity - repeated exposure, Category 2
Specific target organ toxicity - single exposure, Category 3, respiratory tract irritation
Causes skin irritation
May cause an allergic skin reaction
Causes serious eye irritation
Harmful if inhaled
May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause respiratory irritation
Suspected of causing cancer
May cause damage to organs through prolonged or repeated exposure
Contains isocyanates. May produce an allergic reaction

16.6 Training advice

Obtain special instructions and read the Safety Data Sheet before use. Do not handle until all safety precautions have been read and understood. It is recommended that workers are trained in the safe handling of hazardous chemicals

16.7 DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best on the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to is accuracy, reliability or completeness. It is the users responsibility to satisfy themselves as to the suitability of such information for their own particular use