System 300

NEWTON 323-SA Part A: Resin

Sealing Acrylic Injection Resin



Rev 1.0 - 5th March 2019 PRODUCT CODE - 323-SA

SECTION 1. Identification of the Substance/Mixture and of the Company/Undertaking

Product Identifier

Product form Mixture

Product name
 Newton 323-SA Resin

Product codes
 323-SA Resin

Relevant identified uses of the substance and uses advised against

Use of substance/mixture
 Professional use only

Resin constituent in an injection resin for waterproofing

Uses advised against Not for any other use

Details of the Supplier of the Safety Data Sheet

Company Address
 Newton Waterproofing Systems, Newton House, 17-20 Sovereign

Way, Tonbridge, Kent TN9 1RH

Web www.newtonwaterproofing.co.uk

Email address of the competent person

info@newtonwaterproofing.co.uk

Emergency telephone numbers
 Newton Waterproofing systems - English language

+44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

SECTION 2. Hazards Identification

Refer to SECTION 16 for The explanation of the abbreviations used throughout this SDS

The full list of Hazard Phrases & Precautionary Statements stated

throughout this SDS

2.1 Classification of the Substance or Mixture

Classification under Regulation (EC) No. 1272/2008 (CLP)

Acute Tox. 4 (Oral) H302 Acute Tox. 3 (Dermal) H311 Skin Corr. 1A H314 Acute Tox. 4, H332 STOT SE 3 H335

Full text of hazard classes and H-statements: see SECTION 16

Adverse physicochemical, human health and environmental effects

May cause respiratory irritation. Causes skin irritation. Causes serious eye

irritation

2.2 Label Elements

Hazard statements
 As 2.1 Classification under CLP

Signal words (CLP) Warning

Hazard pictograms (CLP)



Hazardous ingredients Methacrylic acid

NEWTON 323-SA Part A: Resin Sealing Acrylic Injection Resin

•	Hazard statements (CLP)	H311 H314 H332	Harmful if swallowed Toxic in contact with skin Causes severe skin burns and eye damage Harmful if inhaled May cause respiratory irritation
•	Precautionary statements (CLP)	P261 P264 P280 P302+P3	Avoid breathing dust, fume, gas, spray, mist, vapours Wash hands, forearms and face thoroughly after handling Wear protective gloves / clothing and eye / face protection 352 IF ON SKIN: Wash with plenty of water
		P303+P3 +P353	361 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower)
		P305+P3 +P338	351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

+P338 Remove contact lenses, if present and easy to do. Continurinsing

P405 Store locked up

P501 Dispose of contents / container to hazardous or special

waste collection point, in accordance with local, regional,

national and/or international regulation

• Other To be handled and used in accordance with good occupational hygiene and safety practice. Wear PPE as SECTION 8.2, handle and store as SECTION

7, manage accidental release as SECTION 6 and follow the instructions in

the Data Sheet

2.3 Other Hazards

PBT / vPvB No additional information available

Other Hazards NDA

Other information
 Classification and labelling have been made on the basis of safety data

sheets of the raw materials that make up the product

SECTION 3. Composition/information on ingredients

3.2 Mixture

NB

This product is a mixture

Hazardous Substances

Chemical name	CAS	EC No.	EC Index- No	REACH Registration Number	%	Classification according to Regulation (EC) No. 1272/2008 (CLP)
Magnesiumacrylate	5698- 98-6				15-25	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Polyethyleneglycodimethacrylate	25852- 47-5				1-5	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Methacrylate acid	79-41- 4	201- 204-4	607- 088- 00-5		1-5	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1A, H314 H314 STOT SE 3, H335

Specific Concentration Limits						
Chemical Name	CAS	EC No	REACH Registration Number	Specific concentration Limits		
Methacrylate acid	79-41-4	201- 204-4	607-088-00-5	(C ≥ 1%) STOT SE 3, H335		

Refer to SECTION 8 for Personal Protection / Exposure Controls

NEWTON 323-SA Part A: Resin

Sealing Acrylic Injection Resin

Refer to SECTION 16 for the full text of Hazard Statements

SECTION 4. First Aid Measures

4.1 Description of First Aid Measures

General
 Never give anything by mouth to an unconscious person. If exposed or

concerned get medical advice / attention. If you feel unwell, seek medical

advice

Those assisting the exposed persons to take no action involving personal risk or without training. Performing mouth-to-mouth can be dangerous,

only to be done by trained personnel

Eye bathing equipment and First Aid Box should be available

Take this SDS with you when seeking medial advice

Skin contact
 Remove contaminated clothing. Gently remove all traces of product and

wash with plenty of soap and water. Continue to rinse for at least 10 minutes. If skin irritation or rash occurs seek medial advice / attention

Eye contact
 Do not rub. Immediately rinse eyes cautiously with plenty of water for at

least 15 minutes holding the eyelids open. Remove contact lenses if present and easy to do so, then continue to rinse cautiously for 15 minutes. Obtain

medical attention if pain, irritation, blinking or redness persists

Ingestion
 Wash out mouth with water. Do NOT induce vomiting. Get emergency

medical attention. If vomiting occurs, the head should be kept forward and low so vomit does not enter the lungs. Never give anything to an unconscious person. Move the exposed person to fresh air. If unconscious, place in the recovery position and get medical advice immediately. Loosen tight clothing such as collar, tie, belt and waistband. Call a doctor or poison

centre if you feel unwell

Inhalation
 Ventilate the area. Remove person from the contaminated place to rest in

fresh air and keep comfortable and breathing. Assure fresh air breathing. Loosen tight clothing such as collar, tie, belt or waistband. If you feel unwell seek medical advice. Call a doctor or poison centre if you feel unwell

Self-protection for first aiders

No action to be taken involving any personal risk or without suitable

training. If it is suspected that the mixture is still present, wear appropriate Personal Protection Equipment, see SECTION 8.2. Wear gloves to remove

contaminated clothing, see SECTION 13 for washing or disposal

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Skin contact May cause moderate irritation. Irritation

Eye contact May cause slight irritation. Eye irritation

Ingestion
 May be harmful if swallowed

Inhalation Harmful if inhaled. May cause respiratory irritation

Delayed / immediate effects
 NDA

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

Immediate / special treatment
 No specific treatment. Treat symptomatically

SECTION 5. Fire-Fighting Measures

5.1 Extinguishing Media Powder, dry power, carbon dioxide, water spray, foam

Unsuitable extinguishing media: No special recommendation

5.2 Special Hazards Arising from the Material

Fire hazard: Combustible after evaporation of all water

Toxic fumes may be released

Page 4 of 38

NEWTON 323-SA Part A: Resin Sealing Acrylic Injection Resin

5.3 Advice for Firefighters

Isolate the affected area

All persons to be immediately removed from the vicinity of the fire. Fire to be dealt with by trained personnel and without involving personal risk

Exercise caution when fighting any chemical fire

Collect the fire fighting water separately. Prevent from entering the environment, waterways, sewers and drains, alert the Environmental Agency if this occurs

Do not enter the area without wearing proper protective equipment, including respiratory protection

Do not attempt to take action without suitable protective equipment. Self contained breathing apparatus. Complete protective clothing

SECTION 6. Accidental Release Measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

General measures
 Do not attempt to take action without wearing suitable personal protection,

refer to SECTION 8.2 of the SDS

Ensure adequate ventilation

Non-emergency personnel Evacuate unnecessary personnel

Do not touch or walk through the spilled material. Ventilate spillage area. Do not breathe dust / fumes/ gas / vapours / mist / spray. Avoid contact

with skin and eyes

• Emergency personnel Evacuate unnecessary personnel and those not wearing the suitable

protection. If outside do not approach from downwind. If outside keep bystanders and passing persons upwind and away from the danger point. Mark out the contaminated area with signage and prevent access by

unauthorised persons

Do not attempt to take action without suitable protective equipment. Equip clean-up crew with proper protection, see SECTION 8 'Exposure controls /

personal protection'

Ensure adequate ventilation, including forced ventilation if in an internal space and necessary, and vent externally to be safely away from other

persons and the general public

Turn leaking containers leak-side up to prevent the escape of material, and place in a sealable leak proof container, label this with the contents

Avoid inhalation of vapours, wear respiratory protection as SECTION 8.2

6.2 Environmental Precautions Prevent the product from entering drains, sewers or watercourses (refer to

SECTION 11). Contain the spillage using bunding

Alert the Environmental Agency in the event of spillage, etc entering water

ways, sewers or drains

6.3 Methods and Materials for Containment and Cleaning Up

Clean-up should ONLY be dealt with by qualified persons familiar with the specific product

Stop the leak if it is safe to do so

Large spillages should be contained by bunding using absorbent materials and carefully transferred into sealable impervious containers. Remnants from large spillages and small spillages should be absorbed and transferred into these containers

Appropriate bunding / absorbent materials: sand, sawdust, universal absorbent and diatomaceous earth

All washings to be retained within the bunding and fully collected up into

NEWTON 323-SA Part A: Resin

Sealing Acrylic Injection Resin

sealable impervious waste container(s), label these with the contents

All contaminated bunding, including all suspected of being contaminated,

to be collected up and transferred to these waste containers

All containers to be labelled and held for disposal as SECTION 13

6.4 Reference to Other Sections Refer to SECTIONS 8 (Personal Protection / Exposure Controls),

12 (Ecological Information) and 13 (Disposal Consideration) of the SDS

SECTION 7. Handling and Storage

7.1 Precautions for Safe Handling

Wear protective equipment as required by use- see SECTION 8 a. Safe handling

> Do not get in eyes, on skin or on clothing - see SECTION 8 for the protection of work clothing. Obtain special instructions before use. Do not handle or use until all safety precautions have been read and understood.

Only use outdoors or in well ventilated areas Do not breathe vapours, aerosols or gases

b. Hygiene measures Do not eat, drink or smoke when handling. Wash hands and other exposed

> areas with mild soap and water after using the material and remove contaminated clothing and protective equipment before entering areas where food and drink are consumed and when leaving the work site

Contaminated work clothing should not be allowed out of the work site. See SECTION 13 for the protection of work clothing and the washing or disposal

of contaminated work clothing and boots

Prevention of handling incompatible substances or mixtures

Do not handle other substances or mixtures at the same time. Keep away from other substances and mixtures

Operations and conditions that could create new risks

Do not allow opened, part used or the container in use to come into contact with other materials including all surfaces around. Ensure the containers are securely sealed during transport, storage and when at the work site

Reduce risk of release to the environment

Avoid spillage. Ensure the floor at storage, transport and the work location will not allow access to drains or water courses. Lay heavy gauge plastic sheeting or similarly impervious protective covering when mixing and dispensing. Contain and clean up spillage as SECTION 6.3 of the SDS

7.2 Conditions for Safe Storage, Including Any Incompatibilities

Store in a well ventilated locked area, keep cool and away from direct Storage conditions

sunlight. Only store in original containers. Keep container tightly closed. The floor of the storage area to be impermeable to prevent the escape of

spillage

Maximum storage / use period: Refer to the 'Best Before' date on the Maximum storage period

container label

Use of the stock should be by Best Before date rotation, using the oldest dates first. Containers past their Best Before date should be removed for

disposal according to SECTION 13 of the SDS

Control of the effects of weather, ambient pressure, temperature, sunlight, humidity and vibration

Protect especially from direct sunlight (UV) and high temperatures

Protect from freezing, frost and heat. Keep away from sources of ignition,

open flames or excessive heat

Ensure containers are securely closed against vibration spillage during transport when loading / unloading vehicles, during transport and moving

NEWTON 323-SA Part A: Resin Sealing Acrylic Injection Resin

from vehicle to the work location. Unopened containers to be protected against damage during these movements

Storage with other substances and mixtures including any incompatibles

Only store in the original packaging. Store against falling / touching other

materials and in an allocated location

Incompatibles: Radical forming substances, reducing agents, metal ions

Storage room design, quantity limits, ventilation and packaging compatibilities

Storage room to be dry, ventilated, and constructed to have impermeable floors and walls to prevent the escape of spillages into the environment

Other considerations No other data available

7.3 Specific End Use(es) Part A of an injection resin for waterproofing. Refer to the Technical Data

Sheet for further information

SECTION 8. Personal Protection/Exposure Control

8.1 Control Parameters

Workplace Exposure Limits (WEL)

EH40: Taken from the HSE EH40/2005 (3rd edition, published 2018):

- not stated = not on EH40

- if no 15 min STEL, 3x TWA used

Carc: Capable of causing cancer and / or heritable genetic damage

Sen: Capable of causing occupational asthma

Can be absorbed through the skin. The assigned substances

are those for which there are concerns that dermal absorption will lead to systematic toxicity

Substance & CAS	limit (8	n exposure hr TWA e period)	Short-term exposure limit (15 minute reference period)		Comments	Source		
	ppm	mg / m³	"		The Carc, Sen and Sk notations are not exhaustive. Notations have been applied to substances identified in IOELV Directives			
Methacrylate	acid							
79-41-4	20	72	40	143	-	HSE EH40 Table		
Polyethylene	Polyethyleneglycodimethacrylate CAS 25852-45-5 and Magnesiumacrylate CAS 5698-98-6							
			Not on t	he FH40 WFI	Table	HSE		

8.2 Exposure Controls

8.2.1 Appropriate Engineering Controls

Ensure there is sufficient ventilation in the area, including forced ventilation Ventilation

if necessary or in an internal or enclosed space, with safe exhaust away from other persons. The floor must be impermeable to prevent the escape of

liquids, laying impermeable protective covering if in doubt

Isolation Isolate the work area with warning signage against unauthorised access.

Ensure all other persons are pre-notified of the works and remain clear of

the work area

Washing Provide eye wash facilities, individual eye wash ampoules and safety shower

Single-Part product, stirring is not required. Work and dispense off Against contamination impervious protective sheeting against splashes onto the person(s) performing this task, any other persons and onto the surrounding areas:

> The person(s) performing this to wear disposable overshoes over their safety work boots when working off the protective sheeting against walking contamination onto the surrounding area

NEWTON 323-SA Part A: Resin

Sealing Acrylic Injection Resin

 When the application is done, dispose of contaminated protective sheeting, the overshoes, etc as controlled waste

. Mists Prevent the fo

Prevent the formation of vapour or aerosol

Do not eat, drink or smoke during stirring or use of the product. Wash hands with soap and water before eating, drinking or smoking and when leaving the work site for natural breaks, break times and at end of day

8.2.2 Personal Protective Equipment

Hygiene & Occupational care

a. Work clothing Impervious disposable 1-piece covering to body, legs and arms with closure

at wrists and ankles, and disposable overshoes

5. Eye / face protection Tight fitting safety goggles, safety glasses with side protection or face visor

EN166

c. Skin protection

(i) Hand Protection

To be impermeable and resistant to the product / substance / mixture. Due to missing tests no recommendation to the glove material can be given

to missing tests no recommendation to the glove material can be given Selection of the glove material to be on consideration of the penetration

times, rates of diffusion and the degradation

Material of gloves The selected protective gloves have to satisfy the specifications of EU

Directive 89/686/EEC, this being repealed by EU 2016/425 on 21/04/2018,

and the resultant standard EN 374

The selection of the suitable gloves does not only depend upon the material, but also further marks of quality and varies from manufacturer to

manufacturer

Break through, and other characteristics, depending upon material density

and the glove type, and must be determined in each case

Gloves to be tightly fitting at the wrists and extend onto the disposable 1-piece covering. Cloves must be inspected prior to each time used and

must be replaced when damaged or worn out

Impervious gloves, chemical resistant: conforming to EN 374

Penetration time of gloves Breakthrough time of the glove material > 4 hours

(ii) Other Chemical resistant safety boots with external feed for the laces, not holes for

the laces

Safety helmet if required, or other head covering, against splashes

Good hygiene measures should be followed at all time

d. Respiratory protection Mouth & nose filter face mask to EN149:2001

In the case of inadequate ventilation wear an appropriate gas filter (i.e. type

A according to EN 14387) is worn

Mist formation; wear protection as for inadequate ventilation

e. Thermal hazards NDA

Environmental exposure measures Avoid release to the environment

g. Hygiene measures Wash thoroughly after handling. Do NOT eat, drink or smoke while using

this product. Remove contaminated clothing, see SECTION 13 for

the washing or disposal of contaminated clothing

SECTION 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Appearance (i) Form Liquid
 (ii) Colour Violet

Odour
 Characteristic odour

NEWTON 323-SA Part A: Resin

Sealing Acrylic Injection Resin

•	Odour threshold	NDA
•	рН	6.5-8
•	Melting point/range °C	N/A
•	Freezing point/range °C	NDA
•	Initial boiling point/range °C	NDA
•	Flash point/self-ignition °C	NDA
•	Evaporation rate	NDA
•	Flammability (solid, gas)	N/A
•	Flammability limits, lower %	NDA
•	Flammability limits, upper %	NDA
•	Auto flammability °C	NDA
•	Decomposition temperature	NDA
•	Explosive properties	NDA
•	Explosive limits	NDA
•	Oxidising properties	NDA
•	Vapour pressure	NDA
•	Relative vapour density at 20°C	NDA
•	Relative density	1.15 g/ml
•	Specific weight	NDA
•	Solubility in water	Soluble material / quickly disperses in water
•	Partition coefficient n-octanol/water	NDA
•	Also soluble in	NDA
•	Viscosity, kinematic	16.552 mm²/s
•	Viscosity, dynamic	19 mPa.s

VOC g/l

NOTE:

The above values related to physiochemical properties are typical values for this product and should not, therefore, be construed as a specification

9.2 Other Information

SECTION 10. Stability and Reactivity

10.1 Reactivity

10.2 Chemical Stability Stable under recommended transport or storage conditions and when

protected against the materials or conditions listed in SECTIONS 10.1 and

NDA

Protect against direct sunlight (UV)

10.3 Possibility of Hazardous Reactions In the presence of radical forming substances (e.g. peroxides, reducing

substances and / or metal ions), a polymerisation with heat dissipation is

possible

10.4 Conditions to Avoid High temperatures. Moisture

10.5 Incompatible Materials to Avoid Radical forming substances, reducing agents, metal ions

NDA. No decomposition occurs if stored, used and applied as directed by **10.6 Hazardous Decomposition Products**

Technical Data Sheet

NEWTON 323-SA Part A: Resin Sealing Acrylic Injection Resin

SECTION 11. Toxicological Information

11.1 Information on Toxicological Effects

Acute toxicity Acute toxicity (oral): Not classified

Acute toxicity (dermal): Not classified Acute toxicity (inhalation): Not classified

In the absence of experimental toxicological data on the product itself, the potential risks to health were evaluated based on the properties of the constituent substances, according to the criteria laid down by the relevant

regulations for Classification

Hazardous ingredients

Substance	Route	Test	Species	Value
CAS 79-41-4 Methacrylate acid	Oral	LD50	Rat	1,060 mg/kg
	Dermal	LD50	Rabbit	500 mg/kg

Relevant hazards for product

Hazard	Negative Symptoms		
Serious eye damage / irritation Causes serious eye irritation. pH 6.5-8			
Skin corrosion / irritation	Causes skin irritation		
STOT single exposure	May cause respiratory irritation		

Other hazards

Hazard	Basis
Acute toxicity - oral	NDA
Acute toxicity - dermal	NDA
Acute toxicity - inhalation	NDA
Ingestion	NDA
Respiratory hazard / inhalation	Not classified
Skin sensitisation	Not classified
Carcinogenicity	Not classified
Germ cell mutagenicity	Not classified
Reproductive toxicity	Not classified
STOT repeated exposure	Not classified
Aspiration hazard	Not classified

Viscosity, kinematic 16.522 mm²/s

Other information The product was not tested. The data reported here are based on the

manufacturers' SDS which is based on information contained in the safety

data sheets of the raw materials that make up the product

SECTION 12. Ecological Information

12.1 Toxicity

Environment Not considered harmful to aquatic organisms nor to cause long-term

adverse effects to the environment

Aquatic toxicity Acute toxicity: Not classified

Chronic toxicity: Not classified

12.2 Persistence and Biodegradability No additional information available

12.3 Bioaccumulative Potential No additional information available

NEWTON 323-SA Part A: Resin

Sealing Acrylic Injection Resin

12.4 Mobility in Soil No additional information available
 12.5 Results of PBT & vPvT Assessment No additional information available
 12.6 Other Adverse Effects No additional information available

Avoid release to the environment

12.7 Additional information The product was not tested. The data reported here are based on the

manufacturers' SDS which is based on information contained in the safety

data sheets of the raw materials that make up the product

No other information available

SECTION 13. Disposal Considerations

13.1 Waste Treatment Methods

Recovery operations
 Treat as SECTION 6: Accidental Release Measures

Disposal operations
 Dispose at approved waste collection sites as controlled waste

Disposal of packaging
 25kg plastic drum with screw cap so cannot access internally to clean,

dispose to controlled waste disposal and including recycling if possible by

them

Waste code number
 17 09 03*: Part A, mixed Parts A+B and wet & solidified product (all Parts)

17 02 04*: Packaging Plastic drum with Part A remnants

Special precautions for the disposal method

Ensure substances or mixtures are not mixed with other materials and if held in the same outer container with other materials all are in separate

sealed containers within the outer container

NB The user's attention is drawn to the possible existence of regional or

national regulations regarding disposal

SECTION 14. Transport Information

ADR	IMDG	IATA	ADN	RID		
14.1 UN Number			•			
N/A	N/A	N/A	N/A	N/A		
14.2 UN proper shippi	ng name					
N/A	N/A	N/A	N/A	N/A		
14.3 Transport hazard	class(es)		•			
N/A	N/A	N/A	N/A	N/A		
14.4 Packing group			,			
N/A	N/A	N/A	N/A	N/A		
14.5 Environmental hazards						
N/A	N/A	N/A	N/A	N/A		
No supplementary info	ormation available	•				

4.6 Special Precautions for User

•	Overland transport	N/A
•	Transport by sea	N/A
•	Air transport	N/A
•	Inland waterway transport	N/A
•	Rail transport	N/A

NEWTON 323-SA Part A: Resin

Sealing Acrylic Injection Resin

14.7 Transport in Bulk According to:

(i) Annex II of Marpol N/A
(ii) the IBC Code N/A

SECTION 15. Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture or Article

COMMISSION REGULATIONS (EC) No 1272/2008 and (EU) No 2015/830 of 28/05/2015 amending Regulation (EC) No 1907/2006 and repealing (EU) 453/2010 20 May 2010 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Other regulations, limitations and prohibitive regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No. 1907/2006:				
3(b). Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No. 1272/2008: Hazard classes - 3.1 to 3.6, - 3.7 adverse effects on sexual function and fertility or on development, - 3.8 effects other than narcotic effects, - 3.9 and 3.10	Polyethyleneglycoldimethacrylate - Magnesiumacrylate			
3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No. 1272/2008	Polyethyleneglycoldimethacrylate - Magnesiumacrylate			

Contains no substances on the REACH candidate list

Contains no REACH Annex XIV substance

Directive 2012/18/EU (SEVESO III)

15.2 Chemical Safety Assessment A chemical safety assessment has not been carried out. Data from the

component substances is included in this SDS

SECTION 16. Other Information

16.1 Basis of this SDS The data reported here are based on the manufacturer's SDS which is based

on information contained in the safety data sheets of the raw materials that

make up the product

16.2 Changes Compared to the Previous Version

Date	Replaces	Sections	Item	Change	Comment
05/03/19	N/A				This is the 1st issue, read the entire document

16.3 Key literature and sources of data Regulation (EC) 1907/2006

Regulation (EC) No. 1272/2008 Regulation (EU) No. 2015/830

Supplier SDS

ECHA, including REACH dossier for component substances

EH40/2005 3rd Edition, 2018

16.4 Abbreviations & Acronyms CLP: EU Regulation 1272/2008: Classification, Labelling & packaging of

chemical substances

HSE: (UK) Health & Safety Executive

NEWTON 323-SA Part A: Resin Sealing Acrylic Injection Resin

IBC Code: International Building Code LD50: Lethal dose, 50% affected

MARPOL: International Convention for the Prevention of Pollution from

Ships

N/A: Not Applicable NDA: No Data Available

PBT: Persistent, Bioaccumulative and Toxic substances vPvB: Very Persistent and very Bioaccumulative substances REACH: Registration, Evaluation, Authorisation and Restriction of

Chemicals: Regulation (EC) No 1907/2006

SDS: Safety Data Sheet

STEL: Short Term Exposure Limit

STOT RE: Specific target organ toxicity (from) repeated exposure STOT SE: Specific target organ toxicity (from) single exposure

TWA: Time Weighted Averages VOC: Volatile organic compounds

16.5 Full text of H and EUH statements

Acute Tox. 3 (Dermal)	Acute toxicity (Dermal), Category 3			
Acute Tox. 4 (Oral)	Acute toxicity (Oral), Category 4			
Eye Irrit. 2	Serious eye damage / irritation, Category 2			
Skin Corr. 1A	Skin corrosion / irritation, Category 1A			
Skin Irrit. 2	Skin corrosion / irritation, Category 2			
STOT SE 3	Specific target organ toxicity - single exposure, Category 3, respiratory tract irritation			
H302	Harmful if swallowed			
H311	Toxic in contact with skin			
H314	Causes severe skin burns and eye damage			
H315	Causes skin irritation			
H319	Causes serious eye irritation			
H332	Harmful if inhaled			
H335	May cause respiratory irritation			

16.6 Training advice

Obtain special instructions and read the Safety Data Sheet before use. Do not handle until all safety precautions have been read and understood. It is recommended that workers are trained in the safe handling of hazardous chemicals

16.7 DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best on the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to is accuracy, reliability or completeness. It is the users responsibility to satisfy themselves as to the suitability of such information for their own particular use

System 300

NEWTON 323-SA Part B: Catalyst





Rev 1.0 - 5th March 2019 PRODUCT CODE - 323-SA

SECTION 1. Identification of the Substance/Mixture and of the Company/Undertaking

Product Identifier

Product form Mixture

Product name
 Newton 323-SA Catalyst

Product codes
 323-SA Catalyst

Relevant identified uses of the substance and uses advised against

Use of substance/mixture
 Professional use only

Catalyst constituent in an injection resin for waterproofing

Uses advised against
 Not for any other use

Details of the Supplier of the Safety Data Sheet

Company Address Newton Waterproofing Systems, Newton House, 17-20 Sovereign

Way, Tonbridge, Kent TN9 1RH

Web www.newtonwaterproofing.co.uk

Email address of the competent person

info@newtonwaterproofing.co.uk

Emergency telephone numbers
 Newton Waterproofing systems - English language

+44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

SECTION 2. Hazards Identification

Refer to SECTION 16 for The explanation of the abbreviations used throughout this SDS

The full list of Hazard Phrases & Precautionary Statements stated

throughout this SDS

2.1 Classification of the Substance or Mixture

Classification under Regulation (EC) No. 1272/2008 (CLP)

Not classified

Full text of hazard classes and H-statements: see SECTION 16

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not represent any particular risk, provided it is handles and used in accordance with good occupational

hygiene and safety practice

2.2 Label Elements

Hazard statements
 No labelling applicable

Signal words (CLP) N/A
 Hazard pictograms (CLP) N/A
 Hazardous ingredients N/A
 Hazard statements (CLP) N/A
 Precautionary statements (CLP) N/A

Other To be handled and used in accordance with good occupational hygiene and

safety practice. Wear PPE as SECTION 8.2, handle and store as SECTION 7, manage accidental release as SECTION 6 and follow the instructions in

the Data Sheet

2.3 Other Hazards

PBT / vPvB No additional information available

Other Hazards NDA

Other information Classification and labelling have been made on the basis of safety data

sheets of the raw materials that make up the product

SECTION 3. Composition/information on ingredients

3.2 Mixture This product is a mixture

Hazardous Substances

Chemical name	CAS	EC No.	EC Index- No	REACH Registration Number	%	Classification according to Regulation (EC) No. 1272/2008 (CLP)
Triethanolamine	102- 71-6	203- 049-8			60-80	Not classified

NB Refer to SECTION 8 for Personal Protection / Exposure Controls

Refer to SECTION 16 for the full text of Hazard Statements

SECTION 4. First Aid Measures

4.1 Description of First Aid Measures

General Never give anything by mouth to an unconscious person. If exposed or concerned get medical advice / attention. If you feel unwell, seek medical

advice

Those assisting the exposed persons to take no action involving personal risk or without training. Performing mouth-to-mouth can be dangerous,

only to be done by trained personnel

Eye bathing equipment and First Aid Box should be available

Take this SDS with you when seeking medial advice

Remove contaminated clothing. Gently remove all traces of product and Skin contact

wash with plenty of soap and water. Continue to rinse for at least 10

minutes. If skin irritation or rash occurs seek medial advice / attention

Do not rub. Immediately rinse eyes cautiously with plenty of water for at Eye contact

least 15 minutes holding the eyelids open. Remove contact lenses if present and easy to do so, then continue to rinse cautiously for 15 minutes. Obtain

medical attention if pain, irritation, blinking or redness persists

Wash out mouth with water. Do NOT induce vomiting. Get emergency Ingestion

medical attention. If vomiting occurs, the head should be kept forward and low so vomit does not enter the lungs. Never give anything to an unconscious person. Move the exposed person to fresh air. If unconscious, place in the recovery position and get medical advice immediately. Loosen tight clothing such as collar, tie, belt and waistband. Call a doctor or poison

centre if you feel unwell

Inhalation Ventilate the area. Remove person from the contaminated place to rest in

> fresh air and keep comfortable and breathing. Assure fresh air breathing. Loosen tight clothing such as collar, tie, belt or waistband. If you feel unwell

seek medical advice. Call a doctor or poison centre if you feel unwell

Self-protection for first aiders No action to be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate

Personal Protection Equipment, see SECTION 8.2. Wear gloves to remove

contaminated clothing, see SECTION 13 for washing or disposal

Page 15 of 38

NEWTON 323-SA Part B: Catalyst Sealing Acrylic Injection Resin

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Skin contact
 Eye contact
 Ingestion
 Inhalation
 May cause moderate irritation
 May cause slight irritation
 May be harmful if swallowed
 Inhalation
 May cause respiratory irritation

Delayed / immediate effects
 NDA

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

Immediate / special treatment
 No specific treatment. Treat symptomatically

SECTION 5. Fire-Fighting Measures

5.1 Extinguishing Media spray,

Powder, alcohol-resistant foam, dry power, carbon dioxide, water

foan

Unsuitable extinguishing media: Do not use a heavy water stream

5.2 Special Hazards Arising from the Material

Toxic fumes may be released

Decomposition products: Carbon monoxide, carbon dioxide, nitrogen

oxides

5.3 Advice for Firefighters Isolate the affected area

All persons to be immediately removed from the vicinity of the fire. Fire to be dealt with by trained personnel and without involving personal risk

Exercise caution when fighting any chemical fire

Collect the fire fighting water separately. Prevent from entering the

environment, waterways, sewers and drains, alert the Environmental Agency

if this occurs

Do not enter the area without wearing proper protective equipment,

including respiratory protection

Do not attempt to take action without suitable protective equipment. Self

contained breathing apparatus. Complete protective clothing

SECTION 6. Accidental Release Measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

General measures
 Do not attempt to take action without wearing suitable personal protection,

refer to SECTION 8.2 of the SDS

Ensure adequate ventilation

Non-emergency personnel
 Evacuate unnecessary personnel

Do not touch or walk through the spilled material. Ventilate spillage area.

Do not breathe dust / fumes/ gas / vapours / mist / spray. Avoid contact

with skin and eyes

• Emergency personnel Evacuate unnecessary personnel and those not wearing the suitable

protection. If outside do not approach from downwind. If outside keep bystanders and passing persons upwind and away from the danger point. Mark out the contaminated area with signage and prevent access by

unauthorised persons

Do not attempt to take action without suitable protective equipment. Equip clean-up crew with proper protection, see SECTION 8 'Exposure controls /

personal protection

Ensure adequate ventilation, including forced ventilation if in an internal space and necessary, and vent externally to be safely away from other persons and the general public

Turn leaking containers leak-side up to prevent the escape of material, and place in a sealable leak proof container, label this with the contents

Avoid inhalation of vapours, wear respiratory protection as SECTION 8.2

6.2 Environmental Precautions Prevent the product from entering drains, sewers or watercourses (refer to

SECTION 11). Contain the spillage using bunding

Alert the Environmental Agency in the event of spillage, etc entering water ways, sewers or drains

6.3 Methods and Materials for Containment and Cleaning Up

Clean-up should ONLY be dealt with by qualified persons familiar with the specific product

Stop the leak if it is safe to do so

Large spillages should be contained by bunding using absorbent materials and carefully transferred into sealable impervious containers. Remnants from large spillages and small spillages should be absorbed and transferred into these containers

Appropriate bunding / absorbent materials: sand, sawdust, universal absorbent and diatomaceous earth

All washings to be retained within the bunding and fully collected up into sealable impervious waste container(s), label these with the contents

All contaminated bunding, including all suspected of being contaminated, to be collected up and transferred to these waste containers

All containers to be labelled and held for disposal as SECTION 13

6.4 Reference to Other Sections Refer to SECTIONS 8 (Personal Protection / Exposure Controls),

12 (Ecological Information) and 13 (Disposal Consideration) of the SDS

SECTION 7. Handling and Storage

7.1 Precautions for Safe Handling

a. Safe handling Wear protective equipment as required by use- see SECTION 8

Do not get in eyes, on skin or on clothing - see SECTION 8 for the protection of work clothing. Obtain special instructions before use. Do not handle or use until all safety precautions have been read and understood. Only use outdoors or in well ventilated areas

Do not breathe vapours, aerosols or gases

Do not eat, drink or smoke when handling. Wash hands and other exposed

areas with mild soap and water after using the material and remove contaminated clothing and protective equipment before entering areas where food and drink are consumed and when leaving the work site

Contaminated work clothing should not be allowed out of the work site. See SECTION 13 for the protection of work clothing and the washing or disposal of contaminated work clothing and boots

c. Prevention of handling incompatible substances or mixtures

Do not handle other substances or mixtures at the same time. Keep away from other substances and mixtures

d. Operations and conditions that could create new risks

Do not allow opened, part used or the container in use to come into contact with other materials including all surfaces around. Ensure the containers are securely sealed during transport, storage and when at the work site

Reduce risk of release to the environment

Avoid spillage. Ensure the floor at storage, transport and the work location will not allow access to drains or water courses. Lay heavy gauge plastic sheeting or similarly impervious protective covering when mixing and dispensing. Contain and clean up spillage as SECTION 6.3 of the SDS

7.2 Conditions for Safe Storage, Including Any Incompatibilities

a. Storage conditions Store in a well ventilated locked area, keep cool and away from direct

sunlight. Only store in original containers. Keep container tightly closed. The floor of the storage area to be impermeable to prevent the escape of

spillage

b. Maximum storage period Maximum storage / use period: Refer to the 'Best Before' date on the

container label

Use of the stock should be by Best Before date rotation, using the oldest dates first. Containers past their Best Before date should be removed for disposal according to SECTION 13 of the SES

disposal according to SECTION 13 of the SDS

c. Control of the effects of weather, ambient pressure, temperature, sunlight, humidity and vibration

Protect especially from direct sunlight (UV) and high temperatures

Protect from freezing, frost and heat. Keep away from sources of ignition,

open flames or excessive heat

Ensure containers are securely closed against vibration spillage during transport when loading / unloading vehicles, during transport and moving from vehicle to the work location. Unopened containers to be protected against damage during these movements

Storage with other substances and mixtures, including any incompatibles

Incompatibles: Bases, strong acids, oxidising agents

Only store in the original packaging. Store against falling / touching other

materials and in an allocated location

e. Storage room design, quantity limits, ventilation and packaging compatibilities

Storage room to be dry, ventilated, and constructed to have impermeable floors and walls to prevent the escape of spillages into the environment

Other considerations No other data available

7.3 Specific End Use(es) Part B of an injection resin for waterproofing. Refer to the Technical Data

Sheet for further information

SECTION 8. Personal Protection/Exposure Control

8.1 Control Parameters

Workplace Exposure Limits (WEL) EH40: Taken from the HSE EH40/2005 (3rd edition, published 2018):
- not stated = not on EH40, if no 15 min STEL, 3x TWA used

Carc: Capable of causing cancer and / or heritable genetic damage

Sen: Capable of causing occupational asthma

Sk: Can be absorbed through the skin. The assigned substances

are those for which there are concerns that dermal

absorption will lead to systematic toxicity

The Carc, Sen and Sk notations are not exhaustive. Notations have been applied to substances identified in IOELV Directives

Substance & CAS	limit (8	n exposure hr TWA e period)	limit (15	n exposure 5 minute e period)	Carc, Sen & Sk Comments	Source
	ppm	mg / m³	ppm mg/m³			
Triethanolamine CAS 102-71-6				Not on th	e EH40 WEL Table	HSE

8.2 Exposure Controls

Isolation

Washing

Mists

d. Against contamination

8.2.1 Appropriate Engineering Controls

a. Ventilation

Ensure there is sufficient ventilation in the area, including forced ventilation if necessary or in an internal or enclosed space, with safe exhaust away from other persons. The floor must be impermeable to prevent the escape of liquids, laying impermeable protective covering if in doubt

Isolate the work area with warning signage against unauthorised access. Ensure all other persons are pre-notified of the works and remain clear of the work area

Provide eye wash facilities, individual eye wash ampoules and safety shower

Part B of a multi-part product, stirring is. Work and dispense off impervious protective sheeting against splashes onto the person(s) performing this task, any other persons and onto the surrounding areas:

- The person(s) performing this to wear disposable overshoes over their safety work boots when working off the protective sheeting against walking contamination onto the surrounding area
- When the application is done, dispose of contaminated protective sheeting, the overshoes, etc as controlled waste

Prevent the formation of vapour or aerosol

Do not eat, drink or smoke during stirring or use of the product. Wash hands with soap and water before eating, drinking or smoking and when leaving the work site for natural breaks, break times and at end of day

8.2.2 Personal Protective Equipment

Hygiene & Occupational care

a. Work clothing

b. Eye / face protection

Skin protection(i) Hand Protection

Material of gloves

Impervious disposable 1-piece covering to body, legs and arms with closure at wrists and ankles, and disposable overshoes

Tight fitting safety goggles, safety glasses with side protection or face visor EN166

To be impermeable and resistant to the product / substance / mixture. Due to missing tests no recommendation to the glove material can be given Selection of the glove material to be on consideration of the penetration times, rates of diffusion and the degradation

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC, this being repealed by EU 2016/425 on 21/04/2018, and the resultant standard EN 374

The selection of the suitable gloves does not only depend upon the material, but also further marks of quality and varies from manufacturer to manufacturer

Break through, and other characteristics, depending upon material density and the glove type, and must be determined in each case

Gloves to be tightly fitting at the wrists and extend onto the disposable 1-piece covering. Cloves must be inspected prior to each time used and must be replaced when damaged or worn out

Impervious gloves, chemical resistant: conforming to EN 374

Penetration time of gloves

Breakthrough time of the glove material > 4 hours

(ii) Other

Chemical resistant safety boots with external feed for the laces, not holes for the laces

Safety helmet if required, or other head covering, against splashes

Good hygiene measures should be followed at all time

d. Respiratory protection Mouth & nose filter face mask to EN149:2001

NEWTON 323-SA Part B: Catalyst

Sealing Acrylic Injection Resin

In the case of inadequate ventilation wear an appropriate gas filter (i.e. type

A according to EN 14387) is worn

Mist formation; wear protection as for inadequate ventilation

e. Thermal hazards NDA

f. Environmental exposure measures Avoid release to the environment

g. Hygiene measures Wash thoroughly after handling. Do NOT eat, drink or smoke while using

this product. Remove contaminated clothing, see SECTION 13 for

the washing or disposal of contaminated clothing

SECTION 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

•	Appearance	(i) Form	Liquid
		(ii) Colour	Clear

Odour Characteristic odour

Odour threshold
 pH
 NDA
 NDA
 Melting point/range °C
 Freezing point/range °C
 Initial boiling point/range °C
 Flash point/self-ignition °C
 NDA

Flash point/self-ignition °C NDAEvaporation rate NDA

Flammability (solid, gas) N/A

Flammability limits, lower % NDAFlammability limits, upper % NDA

Auto flammability °C NDA

Decomposition temperature NDA

Explosive properties NDA

Explosive limits
 NDA

Oxidising properties NDAVapour pressure NDA

Relative vapour density at 20°C

NDA

Relative vapour density at 20 C NDA

Relative density 1.11 g/mlSpecific weight NDA

• Solubility in water NDA

Partition coefficient n-octanol/water NDA
 Also soluble in NDA

Viscosity, kinematic
 Viscosity, dynamic
 22 mPa.s

Viscosity, dynamic 22 mVOC g/l NDA

NOTE: The above values related to physiochemical properties are typical values

for this product and should not, therefore, be construed as a specification

9.2 Other Information NDA

NEWTON 323-SA Part B: Catalyst

Sealing Acrylic Injection Resin

SECTION 10. Stability and Reactivity

10.1 Reactivity None

10.2 Chemical Stability Stable under recommended transport or storage conditions and when

protected against the materials or conditions listed in SECTIONS 10.1 and

10.3

10.3 Possibility of Hazardous Reactions No dangerous reactions known under normal conditions of use

10.4 Conditions to Avoid None known

10.5 Incompatible Materials to Avoid Bases, strong acids, oxidising agents

10.6 Hazardous Decomposition Carbon monoxide, carbon dioxide, nitrogen oxides

Products

SECTION 11. Toxicological Information

11.1 Information on Toxicological Effects

Acute toxicity Acute toxicity (oral): Not classified

Acute toxicity (dermal): Not classified Acute toxicity (inhalation): Not classified

In the absence of experimental toxicological data on the product itself, the potential risks to health were evaluated based on the properties of the constituent substances, according to the criteria laid down by the relevant

regulations for Classification

Hazardous ingredients NDA
Relevant hazards for product NDA

Other hazards

Hazard	Basis
Acute toxicity - oral	Not classified
Acute toxicity - dermal	Not classified
Acute toxicity - inhalation	Not classified
Ingestion	NDA
Serious eye damage / irritation	Not classified
Skin corrosion / irritation	Not classified
Respiratory hazard / inhalation	Not classified
Skin sensitisation	Not classified
Carcinogenicity	Not classified
Germ cell mutagenicity	Not classified
Reproductive toxicity	Not classified
STOT single exposure	Not classified
STOT repeated exposure	Not classified
Aspiration hazard	Not classified

Viscosity, kinematic 19.82 mm²/s

Other information The product was not tested. The data reported here are based on the

manufacturers' SDS which is based on information contained in the safety

data sheets of the raw materials that make up the product

SECTION 12. Ecological Information

12.1 Toxicity

Environment / Ecology NDA

Not classified Aquatic toxicity Acute toxicity:

> Chronic toxicity: Not classified

12.2 Persistence and Biodegradability No additional information available

12.3 Bioaccumulative Potential No additional information available

12.4 Mobility in Soil No additional information available

12.5 Results of PBT & vPvT Assessment No additional information available

12.6 Other Adverse Effects No additional information available

Avoid release to the environment

12.7 Additional information The product was not tested. The data reported here are based on the

manufacturers' SDS which is based on information contained in the safety

data sheets of the raw materials that make up the product

No other information available

SECTION 13. Disposal Considerations

13.1 Waste Treatment Methods

Treat as SECTION 6: Accidental Release Measures Recovery operations

Disposal operations Dispose at approved waste collection sites as controlled waste

Disposal of packaging 2.3kg plastic jerry can with screw cap so cannot access internally to clean,

dispose to controlled waste disposal with recycling if done by them

Waste code number 17 09 03*: Part B, mixed Parts A+B and wet & solidified product (all Parts)

17 02 04*: Packaging Plastic drum with Part B remnants

Special precautions for the disposal method

Ensure substances or mixtures are not mixed with other materials and if held in the same outer container with other materials all are in separate

sealed containers within the outer container

NB The user's attention is drawn to the possible existence of regional or

national regulations regarding disposal

SECTION 14. Transport Information

ADR	IMDG	IATA	ADN	RID
14.1 UN Number				
N/A	N/A	N/A	N/A	N/A
14.2 UN proper shipp	oing name			
N/A	N/A	N/A	N/A	N/A
14.3 Transport hazard	class(es)		•	
N/A	N/A	N/A	N/A	N/A
14.4 Packing group				
N/A	N/A	N/A	N/A	N/A
14.5 Environmental h	azards		•	
N/A	N/A	N/A	N/A	N/A
No supplementary in	formation available	·	•	

NEWTON 323-SA Part B: Catalyst

Sealing Acrylic Injection Resin

14.6 Special Precautions for User

•	Overland transport	N/A
•	Transport by sea	N/A
•	Air transport	N/A
•	Inland waterway transport	N/A
•	Rail transport	N/A

14.7 Transport in Bulk According to:

(i) Annex II of Marpol N/A
(ii) the IBC Code N/A

SECTION 15. Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture or Article

COMMISSION REGULATIONS (EC) No 1272/2008 and (EU) No 2015/830 of 28/05/2015 amending Regulation (EC) No 1907/2006 and repealing (EU) 453/2010 20 May 2010 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Other regulations, limitations and prohibitive regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substances on the REACH candidate list

Contains no REACH Annex XIV substance

Directive 2012/18/EU (SEVESO III)

15.2 Chemical Safety Assessment A chemical safety assessment has not been carried out. Data from the

component substances is included in this SDS

SECTION 16. Other Information

16.1 Basis of this SDS The data reported here are based on the manufacturer's SDS which is based

on information contained in the safety data sheets of the raw materials that

make up the product

16.2 Changes Compared to the Previous Version

Date	Replaces	Sections	Item	Change	Comment
05/03/19	N/A				This is the 1st issue, read the
					entire document

16.3 Key literature and sources of data Regulation (EC) 1907/2006

Regulation (EC) No. 1272/2008 Regulation (EU) No. 2015/830

Supplier SDS

ECHA, including REACH dossier for component substances

EH40/2005 3rd Edition, 2018

16.4 Abbreviations & Acronyms CLP: EU Regulation 1272/2008: Classification, Labelling & packaging of

chemical substances

HSE: (UK) Health & Safety Executive IBC Code: International Building Code LD50: Lethal dose, 50% affected

MARPOL: International Convention for the Prevention of Pollution from

Ships

N/A: Not Applicable NDA: No Data Available

PBT: Persistent, Bioaccumulative and Toxic substances vPvB: Very Persistent and very Bioaccumulative substances REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals: Regulation (EC) No 1907/2006

SDS: Safety Data Sheet

STEL: Short Term Exposure Limit

STOT RE: Specific target organ toxicity (from) repeated exposure STOT SE: Specific target organ toxicity (from) single exposure

TWA: Time Weighted Averages VOC: Volatile organic compounds

16.5 Full text of H and EUH statements N/A

16.6 Training advice

Obtain special instructions and read the Safety Data Sheet before use. Do not handle until all safety precautions have been read and understood. It is recommended that workers are trained in the safe handling of hazardous

chemicals

16.7 DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best on the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to is accuracy, reliability or completeness. It is the users responsibility to satisfy themselves as to the suitability of such information for their own particular use

System 300

NEWTON 323-SA Part C: Initiator





Rev 1.0 - 5th March 2019 PRODUCT CODE - 323-SA

SECTION 1. Identification of the Substance/Mixture and of the Company/Undertaking

Product Identifier

Product form Mixture

Product name
 Newton 323-SA Initiator

Product codes
 323-SA

Relevant identified uses of the substance and uses advised against

Use of substance/mixture Professional use only

Initiator constituent in an injection resin for waterproofing

Uses advised against
 Not for any other use

Details of the Supplier of the Safety Data Sheet

Company Address Newton Waterproofing Systems, Newton House, 17-20 Sovereign

Way, Tonbridge, Kent TN9 1RH

Web www.newtonwaterproofing.co.uk

Email address of the competent person

info@newtonwaterproofing.co.uk

Emergency telephone numbers
 Newton Waterproofing systems - English language

+44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

SECTION 2. Hazards Identification

Refer to SECTION 16 for The explanation of the abbreviations used throughout this SDS

The full list of Hazard Phrases & Precautionary Statements stated

throughout this SDS

2.1 Classification of the Substance or Mixture

Classification under Regulation (EC) No. 1272/2008 (CLP)

Ox. Sol. 3 H272
Acute Tox. 4 (Oral) H302
Skin Irrit. 2 H315
Skin Sens. 1 H317
Eye Irrit. 2 H319
Resp. Sens. 1 H334
STOT SE 3 H335

Full text of hazard classes and H-statements: see SECTION 16

Adverse physicochemical, human health and environmental effects

May intensify fire; oxidiser. Harmful if swallowed. May cause respiratory irritation. Causes skin irritation. May cause an allergic reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled

2.2 Label Elements

Hazard pictograms (CLP)







GHS03

GHS07

GHS08

NEWTON 323-SA Part C: Initiator

Sealing Acrylic Injection Resin

•	Signal	words	(CLP)	Danger
---	--------	-------	-------	--------

Hazard statements (CLP)

H272: May intensify fire

H302: Harmful if swallowed

H315: Causes skin irritation

H317: May cause an allergic skin reaction

H319: Causes serious eye irritation

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335: May cause respiratory irritation

Hazardous ingredients Sodium persulphate

Precautionary statements (CLP) P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking

P220 Keep / Store away from combustible materials
 P261 Avoid breathing dust, fume, gas, spray, mist, vapours
 P280 Wear protective gloves / clothing and eye / face protection

P302+P352 IF ON SKIN: Wash with plenty of water

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable

for breathing

P305+P351 IF IN EYES: Rinse cautiously with water for several minutes. +P338 Remove contact lenses, if present and easy to do. Continue

rinsing

P501 Dispose of contents / container to hazardous or special

waste collection point, in accordance with local, regional,

national and/or international regulation

• Other To be handled and used in accordance with good occupational hygiene and

safety practice. Wear PPE as SECTION 8.2, handle and store as SECTION 7, manage accidental release as SECTION 6 and follow the instructions in

the Data Sheet

2.3 Other Hazards

PBT / vPvB
 ECHA: the substance is not PBT / vPvB

Other Hazards
 NDA

Other information
 Classification and labelling have been made on the basis of safety data

sheets of the raw materials that make up the product

SECTION 3. Composition/information on ingredients

3.2 Mixture

This product is a mixture

Hazardous Substances

Chemical name	CAS	EC No.	EC Index- No	REACH Registration Number	%	Classification according to Regulation (EC) No. 1272/2008 (CLP)
Sodium persulphate (ECHA / REACH name: Disodium peroxodisulphate)	7775- 27-1	231- 892-1			≤100	Ox. Sol. 3, H272 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Resp. Sens. 2, H334 STOT SE 3, H335

NB

Refer to SECTION 8 for Personal Protection / Exposure Controls

Refer to SECTION 16 for the full text of Hazard Statements

NEWTON 323-SA Part C: Initiator

Sealing Acrylic Injection Resin

SECTION 4. First Aid Measures

4.1 Description of First Aid Measures

General
 Never give anything by mouth to an unconscious person. If exposed or concerned get medical advice / attention. If you feel unwell, seek medical

advice

Those assisting the exposed persons to take no action involving personal risk or without training. Performing mouth-to-mouth can be dangerous,

only to be done by trained personnel

Eye bathing equipment and First Aid Box should be available

Take this SDS with you when seeking medial advice

Skin contact
 Remove contaminated clothing. Gently remove all traces of product and

wash with plenty of soap and water. Continue to rinse for at least 10 minutes. If skin irritation or rash occurs seek medial advice / attention

Eye contact
 Do not rub. Immediately rinse eyes cautiously with plenty of water for at

least 15 minutes holding the eyelids open. Remove contact lenses if present and easy to do so, then continue to rinse cautiously for 15 minutes. Obtain

medical attention if pain, irritation, blinking or redness persists

Ingestion
 Wash out mouth with water. Do NOT induce vomiting. Get emergency

medical attention. If vomiting occurs, the head should be kept forward and low so vomit does not enter the lungs. Never give anything to an unconscious person. Move the exposed person to fresh air. If unconscious, place in the recovery position and get medical advice immediately. Loosen tight clothing such as collar, tie, belt and waistband. Call a doctor or poison

centre if you feel unwell

Inhalation
 Ventilate the area. Remove person from the contaminated place to rest in

fresh air and keep comfortable and breathing. Assure fresh air breathing. Loosen tight clothing such as collar, tie, belt or waistband. If you feel unwell

• Self-protection for first aiders No action to be taken involving any personal risk or without suitable

training. If it is suspected that the mixture is still present, wear appropriate Personal Protection Equipment, see SECTION 8.2. Wear gloves to remove

seek medical advice. Call a doctor or poison centre if you feel unwell

contaminated clothing, see SECTION 13 for washing or disposal

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Skin contact
 Causes skin irritation. Irritation. May cause an allergic skin reaction

Eye contact
 May cause slight irritation. Eye irritation

Ingestion Harmful if swallowed

Inhalation
 May cause respiratory irritation. Cough. May cause allergy or asthma

symptoms or breathing difficulties if inhaled

Delayed / immediate effects
 NDA

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

Immediate / special treatment
 No specific treatment. Treat symptomatically

SECTION 5. Fire-Fighting Measures

5.1 Extinguishing Media Dry power, water spray, foam

Unsuitable extinguishing media: Heavy water kit, carbon dioxide

5.2 Special Hazards Arising from the Material

May intensify fire; oxidiser May form explosive peroxides

Page 27 of 3

NEWTON 323-SA Part C: Initiator Sealing Acrylic Injection Resin

Toxic fumes may be released

High temperatures and chemical contamination may liberate gaseous

oxygen causing hazardous pressure increase

5.3 Advice for Firefighters Isolate the affected area

All persons to be immediately removed from the vicinity of the fire. Fire to be dealt with by trained personnel and without involving personal risk

Exercise caution when fighting any chemical fire

Collect the fire fighting water separately. Prevent from entering the environment, waterways, sewers and drains, alert the Environmental Agency

if this occurs

Do not enter the area without wearing proper protective equipment,

including respiratory protection

Do not attempt to take action without suitable protective equipment. Self

contained breathing apparatus. Complete protective clothing

SECTION 6. Accidental Release Measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

General measures
 Do not attempt to take action without wearing suitable personal protection,

refer to SECTION 8.2 of the SDS

Prevent from entering sewers, basements, workpits and any other place

where its accumulation can be dangerous

Allow no open flames, sparks, smoking or any other sources of ignition

Do not use clean-up tools, etc. than may cause sparks

Ensure adequate ventilation

Non-emergency personnel Evacuate unnecessary personnel

Do not touch or walk through the spilled material. Ventilate spillage area.

Do not breathe dust / fumes/ gas / vapours / mist / spray. Avoid contact

with skin and eyes

Emergency personnel
 Evacuate unnecessary personnel and those not wearing the suitable

protection. If outside do not approach from downwind. If outside keep bystanders and passing persons upwind and away from the danger point. Mark out the contaminated area with signage and prevent access by

unauthorised persons

Do not attempt to take action without suitable protective equipment. Equip clean-up crew with proper protection, see SECTION 8 'Exposure controls /

personal protection'

Ensure adequate ventilation, including forced ventilation if in an internal space and necessary, and vent externally to be safely away from other

persons and the general public

Turn leaking containers leak-side up to prevent the escape of material, and

place in a sealable leak proof container, label this with the contents

Avoid inhalation of vapours, wear respiratory protection as SECTION 8.2

6.2 Environmental Precautions Prevent the product from entering drains, sewers or watercourses (refer to

SECTION 11). Contain the spillage using bunding

Alert the Environmental Agency in the event of spillage, etc. entering water

ways, sewers or drains

6.3 Methods and Materials for Containment and Cleaning Up

Clean-up should ONLY be dealt with by qualified persons familiar with the specific product

NEWTON 323-SA Part C: Initiator

Sealing Acrylic Injection Resin

Stop the leak if it is safe to do so

Large spillages should be contained by bunding using absorbent materials and carefully transferred into sealable impervious containers. Remnants from large spillages and small spillages should be absorbed and transferred into these containers

Appropriate bunding / absorbent materials: sand, sawdust, universal absorbent and diatomaceous earth

All washings to be retained within the bunding and fully collected up into sealable impervious waste container(s), label these with the contents

All contaminated bunding, including all suspected of being contaminated, to be collected up and transferred to these waste containers

All containers to be labelled and held for disposal as SECTION 13

6.4 Reference to Other Sections

Refer to SECTIONS 8 (Personal Protection / Exposure Controls),

12 (Ecological Information) and 13 (Disposal Consideration) of the SDS

SECTION 7. Handling and Storage

7.1 Precautions for Safe Handling

a. Safe handling Wear protective equipment as required by use- see SECTION 8

Do not get in eyes, on skin or on clothing - see SECTION 8 for the protection of work clothing. Obtain special instructions before use. Do not handle or use until all safety precautions have been read and understood. Only use outdoors or in well ventilated areas

No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources

Do not breathe vapours, aerosols or gases

b. Hygiene measures Do not eat, drink or smoke when handling. Wash hands and other exposed

areas with mild soap and water after using the material and remove contaminated clothing and protective equipment before entering areas where food and drink are consumed and when leaving the work site

Contaminated work clothing should not be allowed out of the work site. See SECTION 13 for the protection of work clothing and the washing or disposal of contaminated work clothing and boots

c. Prevention of handling incompatible substances or mixtures

Do not handle other substances or mixtures at the same time. Keep away from other substances and mixtures

d. Operations and conditions that could create new risks

Do not allow opened, part used or the container in use to come into contact with other materials including all surfaces around. Ensure the containers are securely sealed during transport, storage and when at the work site

e. Reduce risk of release to the environment

Avoid spillage. Ensure the floor at storage, transport and the work location will not allow access to drains or water courses. Lay heavy gauge plastic sheeting or similarly impervious protective covering when mixing and dispensing. Contain and clean up spillage as SECTION 6.3 of the SDS

7.2 Conditions for Safe Storage, Including Any Incompatibilities

a. Storage conditions Store in a well ventilated locked area, keep cool and out of direct sunlight

Only store in original containers. Keep container tightly closed. Do not store in corrodible metal

in corrodible metal

The floor of the storage area to be impermeable to prevent the escape of spillage

NEWTON 323-SA Part C: Initiator Sealing Acrylic Injection Resin

b. Maximum storage period Maximum storage / use period: Refer to the 'Best Before' date on the container label

Use of the stock should be by Best Before date rotation, using the oldest dates first. Containers past their Best Before date should be removed for disposal according to SECTION 13 of the SDS

c. Control of the effects of weather, ambient pressure, temperature, sunlight, humidity and vibration

Protect especially from direct sunlight and high temperatures

Protect from heat. Keep away from sources of ignition, open flames or

excessive heat

Ensure containers are securely closed against vibration spillage during transport when loading / unloading vehicles, during transport and moving from vehicle to the work location. Unopened containers to be protected against damage during these movements

d. Storage with other substances and mixtures including any incompatibles

Only store in the original packaging. Store against falling / touching other

materials and in an allocated location

Incompatibles: Solvent, oil, reducing agents, bases, acids,, moisture, heat

sources and combustible materials

e. Storage room design, quantity limits, ventilation and packaging compatibilities

Storage room to be dry, ventilated, and constructed to have impermeable floors and walls to prevent the escape of spillages into the environment

f. Other considerations No other data available

7.3 Specific End Use(es) Part C of an injection resin for waterproofing. Refer to the Technical Data

Sheet for further information

SECTION 8. Personal Protection/Exposure Control

8.1 Control Parameters

Workplace Exposure Limits (WEL) EH40: Taken from the HSE EH40/2005 (3rd edition, published 2018):

- not stated = not on EH40

- if no 15 min STEL, 3x TWA used

Carc: Capable of causing cancer and / or heritable genetic damage

Sen: Capable of causing occupational asthma

Sk: Can be absorbed through the skin. The assigned substances

are those for which there are concerns that dermal

absorption will lead to systematic toxicity

Substance & CAS	limit (8	n exposure hr TWA e period)	Short-term exposure limit (15 minute reference period)		Comments	Source
	ppm	mg / m³	ppm mg/m³		The Carc, Sen and Sk notations are not exhaustive. Notations have been applied to substances identified in IOELV Directives	
Sodium persu	Sodium persulphate (ECHA / REACH name: Disodium peroxodisulphate)					
7775-27-1	[Not on the EH40 Table			HSE
///3-2/-1	0.1	NDA	NDA	NDA	NDA	EU

CAS 7775-27-1	Sodium persulphate
Derived No Effect Level (DNEL) / Derived Minimal Effect	Level (DMEL) WORKERS
Acute - systemic effects: Dermal	400 mg/kg body weight/day
Acute - systemic effects: Inhalation	590 mg/m ³

NEWTON 323-SA Part C: Initiator Sealing Acrylic Injection Resin

Acute - local effects: Dermal	2.248 mg/cm ²
Acute - local effects: Inhalation	2.06 mg/m³
Long-term - systemic effects: Dermal	18.2 mg/kg body weight/day
Long-term - systemic effects: Inhalation	2.06 mg/m³
Derived No Effect Level (DNEL) / Derived Minimal Effect	Level (DMEL) GENERAL POPULATION
Acute - systemic effects, dermal	200 mg/kg body weight/day
Acute - systemic effects: Inhalation	295 mg/m ³
Acute - systemic effects: Oral	30 mg/kg body weight/day
Acute - local effects: Dermal	1.124 mg/cm ²
Acute - local effects: Inhalation	295 mg/m³
Long-term - systemic effects: Oral	9.1 mg/kg body weight/day
Long-term - systemic effects: Inhalation	1.03 mg/m³
Long-term - systemic effects: Dermal	9.1 mg/kg body weight/day
Long-term - local effects: Dermal	0.051 mg/cm ²
Long-term - local effects: Inhalation	1.03 mg/m³

CAS 7775-27-1 Sodium persulphate				
Predicted No Effect Concentration (PNEC)				
Environmental Protection Target	Value			
Freshwater	0.076 mg/L			
Intermittent releases (fresh water)	0.763 mg/L			
Freshwater sediment	0.275 mg/kg sediment dw			
Marine water	0.011 mg/L			
Marine water sediment	.0.4 mg/kg sediment dw			
Sewage treatment plant	3.6 mg/L			
Air	No hazard identified			
Soil	0.015 mg/kg soil dw			
Hazard for predators, secondary poisoning	No potential for bioaccumulation			
REACH Dossier (ECHA): Based on the results obtained, s and labelled, according to Directive 67/548 EEC (DSD) a	ubstances of the Persulphate Category were not classified nd to Regulation 1272/2008/EC (CLP)			

8.2 Exposure Controls

8.2.1 Appropriate Engineering Controls

a. Ventilation

b. Isolation

c. Washing

d. Against contamination

Ensure there is sufficient ventilation in the area, including forced ventilation if necessary or in an internal or enclosed space, with safe exhaust away from other persons. The floor must be impermeable to prevent the escape of liquids, laying impermeable protective covering if in doubt

Isolate the work area with warning signage against unauthorised access. Ensure all other persons are pre-notified of the works and remain clear of the work area

Provide eye wash facilities, individual eye wash ampoules and safety shower

Single-Part product, stirring is not required. Work and dispense off impervious protective sheeting against splashes onto the person(s) performing this task, any other persons and onto the surrounding areas:

- The person(s) performing this to wear disposable overshoes over their safety work boots when working off the protective sheeting against walking contamination onto the surrounding area
- When the application is done, dispose of contaminated protective sheeting, the overshoes, etc as controlled waste

NEWTON 323-SA Part C: Initiator

Sealing Acrylic Injection Resin

Prevent the formation of vapour or aerosol Mists

Hygiene & Occupational care Do not eat, drink or smoke during stirring or use of the product. Wash hands with soap and water before eating, drinking or smoking and when

leaving the work site for natural breaks, break times and at end of day

8.2.2 Personal Protective Equipment

a. Work clothing Protective work clothing based on chemical resistance data and assessment of the local exposure potential (Type 4: liquid spray, Type 5: solids, Type 6:

liquid splash)

Example: Impervious disposable 1-piece covering to body, legs and

arms with closure at wrists and ankles, and disposable

Eye / face protection Tight fitting safety goggles, face visor if risk of splashing, EN166

Skin protection

(i) Hand Protection To be impermeable and resistant to the product / substance / mixture. Due to missing tests no recommendation to the glove material can be given

Selection of the glove material to be on consideration of the penetration

times, rates of diffusion and the degradation

Material of gloves The selected protective gloves have to satisfy the specifications of EU

Directive 89/686/EEC, this being repealed by EU 2016/425 on 21/04/2018,

and the resultant standard EN 374

The selection of the suitable gloves does not only depend upon the material, but also further marks of quality and varies from manufacturer to

manufacturer

Break through, and other characteristics, depending upon material density

and the glove type, and must be determined in each case

Gloves to be tightly fitting at the wrists and extend onto the disposable 1-piece covering. Cloves must be inspected prior to each time used and

must be replaced when damaged or worn out

Impervious gloves, chemical resistant: Butyl Rubber conforming to EN 374

Penetration time of gloves Breakthrough time of the glove material > 8 hours

(ii) Other Chemical resistant safety boots with external feed for the laces, not holes for

Safety helmet if required, or other head covering, against splashes

Good hygiene measures should be followed at all time

Mouth & nose filter face mask to EN149:2001 Respiratory protection

In the case of inadequate ventilation wear an appropriate gas filter (i.e. type

A according to EN 14387) is worn

Mist formation; wear protection as for inadequate ventilation

Thermal hazards NDA

Environmental exposure measures Avoid release to the environment

Hygiene measures Wash thoroughly after handling. Do NOT eat, drink or smoke while using

this product. Remove contaminated clothing, see SECTION 13 for

the washing or disposal of contaminated clothing

SECTION 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

(i) Form Solid, fine white powder **Appearance**

> (ii) Colour White

Page 32 of 38

NEWTON 323-SA Part C: Initiator Sealing Acrylic Injection Resin

•	Odour	Odourless		
•	Odour threshold	NDA		
•	рН	3.5-3.8		
•	Melting point/range °C	180°C		
•	Freezing point/range °C N/A			
•	Initial boiling point/range °C NDA			
•	Flash point/self-ignition °C N/A			
•	Evaporation rate	NDA		
•	Flammability (solid, gas)	N/A		
	EI 1 11: 1: 1: 0/	N. (1. 1.1		

Flammability limits, lower %
 Non flammable

Flammability limits, upper % NDA Auto flammability °C N/A 180°C Decomposition temperature Explosive properties NDA **Explosive limits** N/A Oxidising properties NDA NDA Vapour pressure Relative vapour density at 20°C NDA 2 Relative density NDA Specific weight

Soluble in water. Water: 0.55 g/ml

Partition coefficient n-octanol/water NDA
Also soluble in NDA
Viscosity, kinematic NDA
Viscosity, dynamic NDA
VOC q/l NDA

NOTE: The above values related to physiochemical properties are typical values

for this product and should not, therefore, be construed as a specification

9.2 Other Information NDA

SECTION 10. Stability and Reactivity

10.1 Reactivity May cause fire or explosion: strong oxidiser

May cause or intensify fire: oxidiser

10.2 Chemical Stability Stable under recommended transport or storage conditions and when

protected against the materials or conditions listed in SECTIONS 10.1 and

High temperatures and chemical contamination may liberate

10.3

10.3 Possibility of Hazardous Reactions If released it may accelerate the burning of other combustible materials

10.4 Conditions to Avoid Heat. Moisture. Keep away from combustible materials. Avoid contact with

hot surfaces. No flames. No sparks. Eliminate all sources of ignition

10.5 Incompatible Materials to Avoid Solvents, oil, oxidising agents, bases, acids, heat sources moisture,

combustible materials

10.6 Hazardous Decomposition

gaseous

Products oxygen causing hazardous pressure increase

NEWTON 323-SA Part C: Initiator Sealing Acrylic Injection Resin

To be used and applied according to the Technical Data Sheet

SECTION 11. Toxicological Information

11.1 Information on Toxicological Effects

Acute toxicity Acute toxicity (oral): Harmful if swallowed

Acute toxicity (dermal): Not classified Acute toxicity (inhalation): Not classified

In the absence of experimental toxicological data on the product itself, the potential risks to health were evaluated based on the properties of the constituent substances, according to the criteria laid down by the relevant

regulations for Classification

Hazardous ingredients

Sı	ubstance	Route	Test	Species	Value
CAS 7775-27-1 Sc	odium persulphate	Oral	LD50	Rat	920 mg/kg
		Dermal	LD50	Rabbit	10,000 mg/kg
		Inhalation (dust / mist)	LC50	Rat	5.1 mg/L/4 hr

Relevant hazards for product

Hazard	Negative Symptoms
Serious eye damage / irritation	Causes serious eye irritation. pH 3.5-3.8
Skin corrosion / irritation	Causes skin irritation, pH 3.5-3.8
Respiratory hazard / inhalation	May cause allergy or asthma symptoms or breathing difficulties if inhaled
Skin sensitisation	May cause an allergic skin reaction
STOT single exposure	May cause respiratory irritation

Other hazards

Hazard	Basis
Acute toxicity - oral	NDA
Acute toxicity - dermal	NDA
Acute toxicity - inhalation	NDA
Ingestion	NDA
Carcinogenicity	Not classified
Germ cell mutagenicity	Not classified
Reproductive toxicity	Not classified
STOT repeated exposure	Not classified
Aspiration hazard	Not classified

Other information

The product was not tested. The data reported here are based on the manufacturers' SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

SECTION 12. Ecological Information

12.1 Toxicity

Environment Not considered harmful to aquatic organisms nor to cause long-term

adverse effects to the environment

Aquatic toxicity Acute toxicity: Not classified

Chronic toxicity: Not classified

12.2 Persistence and Biodegradability No additional information available

NEWTON 323-SA Part C: Initiator

Sealing Acrylic Injection Resin

12.3 Bioaccumulative Potential No additional information available
 12.4 Mobility in Soil No additional information available
 12.5 Results of PBT & vPvT Assessment No additional information available

ECHA / REACH Dossier: the substance is not PBT/vPvB

12.6 Other Adverse Effects

No additional information available

Avoid release to the environment

12.7 Additional information The product was not tested. The data reported here are based on the

manufacturers' SDS which is based on information contained in the safety

data sheets of the raw materials that make up the product

No other information available

SECTION 13. Disposal Considerations

13.1 Waste Treatment Methods

Recovery operations
 Treat as SECTION 6: Accidental Release Measures

Disposal operations
 Dispose at approved waste collection sites as controlled waste

Disposal of packaging
 Plastic tub with full diameter lid, containing 0.06kg of the Initiator

Waste code number
 17 09 03*: Part C (Initiator), Part C + water and wet & solidified mixed Parts

A+B+C

17 02 04*: Packaging Plastic tub with Part CE remnants

Special precautions for the disposal method

Ensure substances or mixtures are not mixed with other materials and if held in the same outer container with other materials all are in separate

sealed containers within the outer container

NB The user's attention is drawn to the possible existence of regional or

national regulations regarding disposal

SECTION 14. Transport Information

ADR	IMDG	IATA	ADN	RID
14.1 UN Number				
1505	1505	1505 1505 1505		1505
14.2 UN proper shippi	ng name			
Sodium Persulphate	Sodium Persulphate	Sodium Persulphate	Sodium Persulphate	Sodium Persulphate
Transport document d	escription			
UN 1505 Sodium Persulphate, 5.1, III, (E)	e, 5.1, III, Persulphate, 5.1, III Persulphate, 5.1, III Persulphate, 5.1, III		UN 1505 Sodium Persulphate, 5.1, III	
14.3 Transport hazard	class(es)			
5.1	5.1	5.1	5.1	5.1
5.1	5.1	5.1	5.1	5.1
14.4 Packing group				

IIIIIIIIIIII III14.5 Environmental hazards Dangerous for the environment: No environment: No environment: No environment: No environment: No Marine pollutant: No

NEWTON 323-SA Part C: Initiator

Sealing Acrylic Injection Resin

No supplementary information available				
14.6 Special preca			ADR	
Overland	Classification code			O2
transport	Limited quantities			5kg
	Excepted quantiti	es	ADR	E1
	Packing instruction	ons	ADR	P002, IBC08, LP02, R001
	Special packing p	rovisions	ADR	B4
	Mixed packing pr	ovisions	ADR	MP10
	Portable tank and	bulk container instructions	ADR	T1
	Portable tank and	bulk container special provisions	ADR	TP33
	Tank code		ADR	SGAV
	Tank special provi	isions	ADR	TU3
	Vehicle for tank c	arriage		AT
	Transport categor	ry	ADR	3
	Special provisions	s for carriage - Bulk	ADR	VC1, VC2, AP6, AP7
	Special provisions unloading and ha	s for carriage - Loading, andling	ADR	CV24
	Hazard identificat	ion number (Kemler No.)		50
	Orange plates			50 1505
	Tunnel restriction	code	ADR	E
Transport by sea	Limited quantities	5	IMDG	5 kg
	Excepted quantities		IMDG	E11
	Packing instructions		IMDG	P002, LP02
	IBC packing instructions		IMDG	IBC08
	IBC special provis	ions	IMDG	B3
	Tank instructions		IMDG	T1
	Tank special provi	isions	IMDG	TP33
	EmS-No.		Fire	F-A
	EmS-No.		Spillage	S-Q
	Stowage category		IMDG	А
	Segregation		IMDG	SG39, SG49
	Properties and observations (IMDG) Colourless crystals or powder. Soluble in water Mixtures with combustible material are sensitive to friction and are liable ignite Reacts fiercely with cyanides when heated or by friction. May form explosive mixture with powdered metals or ammonium compounds		sitive to friction and are liable to or by friction.	
	MFAG-No	· · ·	IATA	140
			L	

Sealing Acrylic Injection Resin

NEWTON 323-SA Part C: Initiator

Transport by air	PCA Excepted quantities	IATA	E1
	PCA Limited quantities	IATA	Y546
	Limited quantity maximum new quantity	IATA	10 kg
	Packing instructions	IATA	559
	Maximum net quantity	IATA	25 kg
	Packing instructions	CAO	563
	Maximum net quantity	CAO	100 kg
	ERG Code	IATA	5L
Inland waterway	Classification code	ADN	O2
transport	Limited quantities	ADN	5 kg
	Excepted quantities	ADN	E1
	Equipment required	ADN	PP
	Number of blue cones / lights	ADN	0
Rail transport	Classification code	RID	O2
	Limited quantities	RID	5 kg
	Excepted quantities	RID	E1
	Packing instructions	RID	P001, IBC08, LP02, R001
	Special packing provisions	RID	B3
	Mixed packing instructions	RID	MP10
	Portable tank and bulk container instructions	RID	T1
	Portable tank and bulk container special provisions	RID	TP33
	Tank codes for RID tanks	RID	SGAV
	Special provisions for RID tanks	RID	TU3
	Transport category	RID	3
	Special provisions for carriage - Bulk	RID	VC1, VC2, AP6, AP7
	Special provisions for carriage - Loading, unloading and handling	RID	CW24
	Colis express (express parcels)	RID	CE11
	Hazard identification number	RID	50
14.7 Transport in k Code	oulk according to Annex 11 of Marpol and the IBC		N/A

SECTION 15. Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture or Article

COMMISSION REGULATIONS (EC) No 1272/2008 and (EU) No 2015/830 of 28/05/2015 amending Regulation (EC) No 1907/2006 and repealing (EU) 453/2010 20 May 2010 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Other regulations, limitations and prohibitive regulations

Contains no REACH substances with Annex XVII restrictions Contains no substances on the REACH candidate list Contains no REACH Annex XIV substance Directive 2012/18/EU (SEVESO III)

NEWTON 323-SA Part C: Initiator Sealing Acrylic Injection Resin

15.2 Chemical Safety Assessment

A chemical safety assessment has not been carried out. Data from the

component substances is included in this SDS

SECTION 16. Other Information

16.1 Basis of this SDS The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

16.2 Changes Compared to the Previous Version

Date	Replaces	Sections	Item	Change	Comment
05/03/19	N/A				This is the 1st issue, read the entire document

16.3 Key literature and sources of data Regulation (EC) 1907/2006

Regulation (EC) No. 1272/2008 Regulation (EU) No. 2015/830

Supplier SDS

ECHA, including REACH dossier for component substances

EH40/2005 3rd Edition, 2018

16.4 Abbreviations & Acronyms

CLP: EU Regulation 1272/2008: Classification, Labelling & packaging of chemical substances

HSE: (UK) Health & Safety Executive IBC Code: International Building Code

LD50: Lethal dose, 50% affected

LC50: Lethal concentration, 50% affected

MARPOL: International Convention for the Prevention of Pollution from

Ships

N/A: Not Applicable NDA: No Data Available

PBT: Persistent, Bioaccumulative and Toxic substances vPvB: Very Persistent and very Bioaccumulative substances

REACH: Registration, Evaluation, Authorisation and Restriction of

Chemicals: Regulation (EC) No 1907/2006

SDS: Safety Data Sheet

STEL: Short Term Exposure Limit

STOT RE: Specific target organ toxicity (from) repeated exposure STOT SE: Specific target organ toxicity (from) single exposure

TWA: Time Weighted Averages VOC: Volatile organic compounds

16.5 Full text of H and EUH statements

Acute Tox. 4 (Oral)	Acute toxicity (Oral), Category 4
Eye Irrit. 2	Serious eye damage / irritation, Category 2
Ox. Sol. 3	Oxidising solids, Category 3
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion / irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity - single exposure, Category 3, respiratory tract irritation
H272	May intensify fire; oxidiser
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction

NEWTON 323-SA Part C: Initiator Sealing Acrylic Injection Resin

H319	Causes serious eye irritation
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation

16.6 Training advice

Obtain special instructions and read the Safety Data Sheet before use. Do not handle until all safety precautions have been read and understood. It is recommended that workers are trained in the safe handling of hazardous chemicals

16.7 DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best on the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to is accuracy, reliability or completeness. It is the users responsibility to satisfy themselves as to the suitability of such information for their own particular use