

OVERVIEW

Terracoat Stain is a ready mixed pigmented coating designed for application as a topcoat for Terracoat Textured Coatings. It has excellent dirt pick-up resistance and is designed for use in areas where atmospheric pollution is a problem. Terracoat Stain is a low profile coating imparting colour to the surface with minimum film build, thereby allowing the original granular appearance of the Terracoat to be maximized. Terracoat Stain is available in an attractive range of colours.

PROPERTIES

Terracoat Stain is formulated with pure acrylic resins, fade resistant pigments, film preservative to provide a tough weather resistant film with following properties.

- Excellent UV resistance
- Excellent dirt pick-up resistance
- Excellent fade resistance
- High opacity, low profile coating
- Attractive mid sheen finish
- Breathable film
- Easy-to-apply
- Environmentally friendly

AREAS OF USE

Terracoat Stain is designed for use as a topcoating for Terracoat Textured Coating where extra dirt pick-up resistance is required. It can be applied over pigmented and not-pigmented Terracoat. It can also be used as a renovation coating to overcoat old textured coating surfaces after proper pre-treatment.

PREPARATION OF SURFACE

New Terracoat Substrate:

Allow the Terracoat to dry for a period of 72 hours prior to application of Terracoat Stain. No priming is required.

Old textured surfaces:

Check surface for soundness and make good any damages. Remove any flaking material and apply fresh base texture. Clean surface with a soda/water solution and rinse with clean water. Treat any mould, fungus, algae with a sterilizing solution prior to application of a coat of Penetrating Primer.

APPLICATION & CLEANING OF TOOLS

Terracoat Stain is applied on new and old substrates in 2 coats, using spray, roller or brush.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terracoat Stain is supplied in 5kg and 20kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Low profile topcoat for Terracoat Textured Coating,
Binder	Pure acrylic.
Pigments	Fade resistant pigments.
Viscosity	2,000cps
Specific Weight	1.15
Colours	Standard range of colours.
Material Consumption	0.2-0.3kg/m ² in two coats.
Packaging	5kg and 20kg plastic pails.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.
Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.
Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland
Tel: +353 (0) 1 2819 045
Fax: +353 (0) 1 2819 048
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terrakovostok.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP
Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820 101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com