



Handycoat® EZ-Joint™

**Ready-to-use interior filler
for jointing gypsum board**

- Easy handling and application
- Excellent adhesion
- Good crack resistance
- Low shrinkage



ENVIRONMENTALLY
FRIENDLY



Handycoat® EZ-Joint™

Ready-to-use interior filler for jointing gypsum board

Handycoat EZ-Joint is a specifically formulated interior ready to use filler compound for jointing gypsum board. It has excellent application properties and provides a superior bond for embedding tape and glass fibre scrim. It has excellent non-slump properties and is ideal for patching plaster cracks. It can also be used as a general purpose filler for cementitious surfaces.

Benefits

Handycoat EZ-Joint is made from a selected blend of acrylic polymers and precisely graded fillers. This ensures easy handling and application, which allows for excellent adhesion, and with low shrinkage offers good crack resistance.

Areas of use

Handycoat EZ-Joint is primarily designed for jointing gypsum board, but is also suitable for embedding drywall tape and glass fibre scrim, for fixing metal corner beading and for patching plaster cracks.

Application



Apply a thin layer of Handycoat EZ-Joint to the joint and embed tape.

Apply a further layer of Handycoat EZ-Joint and smooth surface.

Finish with Handycoat Interior or Handycoat EZ-Skim.

Wet sanding is recommended using a damp sponge, to avoid dust.

Use 150 grit sandpaper for dry sanding

Product Information


Pack size: 5kg and 25kg

Consumption rates: $\pm 1.7 \text{ kg/m}^2/\text{mm}$

Dilution: With water, up to 0.5lt per 25kg if required

Colour: White

Application method: Spatula



For more information please refer to the Terraco Technical Data Sheet or contact your nearest Terraco representative.

