

OVERVIEW

Handycoat EZ-Joint is an interior ready to use filler specifically formulated for jointing gypsum board. Handycoat EZ-Joint has excellent application properties and provides a superior bond for embedding tape and glass fibre scrim. It has excellent non-slump properties and is ideal for patching plaster cracks.

PROPERTIES

Handycoat EZ-Joint is made from a selected blend of acrylic polymers and precisely graded fillers. Properties include:

- Easy to use
- Excellent adhesion
- Good crack resistance
- Low shrinkage
- Drying time dependant on conditions

AREAS OF USE

Handycoat EZ-Joint is primarily used as a jointing compound for gypsum board for embedding drywall tape and glass fibre scrim. It is also used for fixing metal corner beading and for patching plaster cracks. It can also be used as a general purpose filler for cementitious surfaces.

PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. Under normal use primers and sealers are not required with the exception of oil based paints, for these backgrounds use a suitable primer/sealer as recommended by the paint manufacturer.

APPLICATION & CLEANING OF TOOLS

Mix contents of drum to form a smooth, even paste. Add up to 0.5 ltr water/25kg if required.

Apply a thin layer of compound to the joint and embed tape. Apply a further layer of compound and smooth surface. Finish with Handycoat Interior/Handycoat EZ-Skim.

Wet sanding is recommended using a damp sponge, to avoid dust. Use 150 grit sandpaper for dry sanding.

A partially used pail of Handycoat EZ-Joint can be saved for re-use. Simply clean the sides of the pail, cover with plastic film or cling film and re-seal pail.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Handycoat EZ-Joint is supplied in 5kg and 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 18 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Ready-mixed quick drying filler of inert extenders.
Filler	Precisely graded fillers.
Binder	Styrene acrylate.
Dilution	Water if required, up to 0.5 ltr/25 kg
Density	1.70
Colour	White.
Application	By spatula
Consumption Rate	1.6-1.7Kg/m ² /mm
Cleaning of Tools	With water.
Packaging	5kg and 25kg plastic pails.
Storage	18 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.
Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.
Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland
Tel: +353 (0) 404 66555
Fax: +353 (0) 404 66654
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terraco.khv.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP
Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820 101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com