

DESCRIPTION

CANADER™ is a CE marked (EN 13108-1) tarmac repair material that has been specially formulated to enable first time repairs to carriageways.

AREAS OF USE

CANADER™ is used for the repair of potholes, utility cuts and iron work installations. It can be used in all weathers all year round.

SURFACE PREPARATION

Remove any loose stones, gravel, sand, etc. from the sides and bottom of the hole. If possible, try to provide a clean 25-37 mm vertical edge for binding. **CANADER™**, like hot asphalt, will best adhere to a strong, clean surface. If the pothole is deep enough to be into the road base, compact any loose material with a hand or plate tamper. If the hole extends into a sand or gravel shoulder, provide a 25-37 mm vertical edge in the shoulder to hold the **CANADER™**.

APPLICATION

Fill the area with **CANADER™** and compact in 30mm layers using equipment such as a tarmac tamper. The repair can be trafficked immediately. It is that simple!

TECHNICAL DATA

Product:	Bitumen based cold mix
Colour:	Black
Storage:	Can be kept outside
Shelf Life:	18 months
Packaging:	Available in 25kg bags (48 per pallet), 1 tonne bulk bag or 30 tonne loose loads

CLEANING OF TOOLS AND HANDS

Tools can be cleaned immediately after use with suitable environmentally friendly tar remover. Cleaning of hands, use **Addagrip Organic Hand Cleaner**.

DISPOSAL CONSIDERATIONS

Please consider the regional or national regulations regarding disposal.

HEALTH & SAFETY PRECAUTIONS

Before using this product, please ensure you have been supplied and have read carefully the following:-

1. The hazard label (complying with CLP – European Regulation (EC) No. 1272/2008 on Classification, Labelling and Packaging of substances and mixtures) applied to the container.
2. Safety Data Sheet

HOW TO SPECIFY

CANADER™ is supplied by Addagrip Terraco UK Limited, Addagrip House, Bell Lane Industrial Estate, Uckfield, East Sussex TN22 1QL. Addagrip Terraco UK Limited products are sold subject to the company's Terms and Conditions of Sale, a copy of which is available on request. Whilst Addagrip endeavours to ensure that advice, specifications, recommendations and information given is correct, it cannot have control over how its products are applied and will not accept liability, directly or indirectly, arising from application of its materials. Any advice, recommendation or information given by Addagrip Terraco UK Limited is based on practical experience and is believed to be accurate at the time of publication, no liability or responsibility of any kind (including liability for negligence) is accepted in this respect by the company, its Servants, or Agents. The figures quoted do not constitute a specification. They represent typical values obtained for this product.

JAN 2016